

14260-GREEN

MSDS Number

BFHYT

National Stock Number

8010-00-616-7490

Product Name

14260-GREEN

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:14260-GREEN

MSDS Date:01/01/1985

FSC:8010

NIIN:00-616-7490

MSDS Number: BFHYT

Responsible Party

PRATT AND LAMBERT INC

16116 E 13TH ST

WICHITA , KS 67201

US

Emergency Phone: 716-873-6000 DOT EMER 8002553924

Info Phone: 316-733-1361

Cage: 61196

Contractor

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 45%

ACGIH TLV: 500 PPM

CHROMIUM (III) OXIDE

CAS: 1308-38-9

RTECS: GB6475000

Fraction By Weight:

OSHA PEL0.5 MG/M3 (CR)

ACGIH TLV: 0.5 MG/M3 (CR); 8990

LEAD CHROMATE PIGMENT

Fraction By Weight:

OSHA PEL0.05 MG/M3 (PB)

ACGIH TLV: 0.05MG/M3(CR)A2;8990

TRIETHYLAMINE (SARA III)

CAS: 121-44-8

RTECS: YE0175000

Fraction By Weight:

OSHA PEL25 PPM/15 STEL

ACGIH TLV: 10 PPM/15 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ETHYL KETOXIME

RTECS: PM7783000

Fraction By Weight:

Hazards

Effects of Overexposure:IRRIT OF NOSE,THROAT,EYES & POSS DIZZINESS & NAUSEA.SPRAY MIST CONTN LEAD.

First Aid

First Aid:INHAL:REMOVE FR EXPOSUR & PROVID FRESH AIR.SPLASH EYES-FLUSH IMMED W/LG AMTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV CONTAM CLOTHING & WASH ALL AFFECT AREA W/WATR.INGEST:DO NOT INDUC VOMITNG.CONSULT ADR. IMMED IN ALL CASES.

Fire Fighting

Flash Point:104 F 40 C TCC

Extinguishing Media:CLASS B EXTING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL FOAM

Fire Fighting Procedures:SELF CONTAINED BREATH APPARAT WATER MAY BE INEFFECTIVE.

Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTHLY CLOS.ISOLAT FR HEAT,ELECTR EQPMT,SPARKS & OPN FLAME.DO NOT APPLY TO VRYHOT SUR

Accidental Release

Spill Release Procedures:REMOV ALL SOURCES FO IGNIT (FLAMES,HOT SURFACES,ELECTRICAL, STATIC OR FRICTIONAL SPARKS).VENTILAT AREA & AVOID BREATHING VAPORS.REMOV W/ INERT ABSORB & NON-SPARKING TOOLS.STEPS MUST BE TAKN TO PREVNT CONTAM OF GROUND WATR OR STREAMS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOV 120 F.STORE LG QUANTITIES IN COMPLIA W/OSHA 1910.106.CONTNRS SHLD BE GROUNDED & BONDED TO THE RECEIVING CONTNR.

Other Precautions:DO NOT CUT OR WELD ON EMPTY CONTAINER. DO NOT USE UNTIL ALL SAFETY PRECATIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

Exposure Controls

Respiratory Protection:NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY

WHN SPRAYING IN OUTDR
Ventilation:PROVID GEN DILUT/LOC EXHAUST VENT TO KP CONCENT BELO ACEP
TL
Protective Gloves:SOLVENT,IMPERME
Eye Protection:SAFETY EYEWT
Other Protective Equipment:PROTECTV EQPMT TO PRVNT SKN CONTCT.SE
OSHA,29 CFR 1910.1025
Supplemental Safety and Health

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:311-373F
Vapor Density:>AIR
Evaporation Rate & Reference:Percent Volatiles by Volume:61

Stability

Stability Indicator/Materials to Avoid:YES
AVOID CONTCT W/STRONG ACIDS OR AKALINE MATERIALS.
Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES.
Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE & OXIDES OF
CARBON & LEAD.
Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIV CHEM
W/O TECHN SUPERVISION.

Disposal

Waste Disposal Methods:DISPOSE IN ACCORD W/LOCAL, STATE & FEDERAL
REGULATIONS.INCINERATIN EPA APPRVD FACILITY.DO NOT INCINERAT CLOSED
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.