

## **YELLOW**

### **MSDS Number**

BFKLY

### **National Stock Number**

8010-00-664-1913

### **Product Name**

YELLOW

### **Manufacturer**

AMERON INDUSTRIAL COATINGS DIV

### **Product Identification**

Product ID:YELLOW

MSDS Date:01/01/1987

FSC:8010

NIIN:00-664-1913

MSDS Number: BFKLY

### **Responsible Party**

AMERON INDUSTRIAL COATINGS DIVISION

201 N BERRY ST

BREA , CA 92621-3904

US

Emergency Phone: 714-529-4597

Info Phone: 714-529-4597

Cage: 09869

### **Contractor**

AMERON INDUSTRIAL COATINGS DIVISION

BREA, CA 92621-3904

US

714-529-4597

Cage: 09869

### **Ingredients**

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 7.50%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

Fraction By Weight: 20.3%

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight: 5.00%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 15.0%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

LEAD CHROMATE (VI) OXIDE (OSHA PEL FOR LEAD FROM 29CFR

CAS: 18454-12-1

RTECS: OF9800000

Fraction By Weight: 1.0%

OSHA PEL0.05 MG/M3 (PB)

ACGIH TLV: 0.05MG/M3(CR)A2;8990

## Hazards

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

## First Aid

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CAL A PHYSICIAN IF CONDITIONS PERSIST.

## Fire Fighting

Flash Point:44F TCC

Lower Limits:1.0

Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE

## Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING

## Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.

Other Precautions: CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

## Exposure Controls

Respiratory Protection: USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY

Supplemental Safety and Health

NT8050000 ISOPROPYL ALCOHOL, 5%. RESPIRATOR USE BASED ON CHEM CONC. AND CONDITION OF USE

## Chemical Properties

HCC: F2

Boiling Pt: B.P. Text: 175-246F

Vapor Density: > 1

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 73.0

## Stability

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRE, HEAT AND HOT SURFACES

## Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.