

PR-1005-L

MSDS Number

BFKNQ

National Stock Number

8030-00-664-4019

Product Name

PR-1005-L

Manufacturer

COURTAULDS AEROSPACE INC

Product Identification

Product ID:PR-1005-L
MSDS Date:01/01/1985
FSC:8030
NIIN:00-664-4019
MSDS Number: BFKNQ

Responsible Party

COURTAULDS AEROSPACE INC

757 CALIFORNIA ST

GLENDALE , CA 91203

US

Emergency Phone: 818-549-7973

Info Phone: 818-549-7973

Cage: 83574

Contractor

PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

1800

GLENDALE, CA 91209

US

818-240-2060

Cage: 83574

Ingredients

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 6%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

PHENOLIC RESIN

Fraction By Weight: 9%

ACGIH TLV: UNK

METHYLENE CHLORIDE (DICHLOROMETHANE) (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 30%

OSHA PEL500 PPM; Z-2

ACGIH TLV: 50 PPM, A2; 9394

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ISOBUTYL KETONE (HEXONE) (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 44%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM/75 STEL; 9394

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure: IRRITATION OF EYES & RESPIRATORY TRACT.

First Aid

First Aid: EYES: WASH OUT WITH PLENTY OF WATER - SEE A PHYSICIAN. SKIN: WASH THOROUGHLY WITH SOAP & WATER. INHALATION: REMOVE PERSONNEL TO FRESH AIR.

Fire Fighting

Flash Point: 53F 12C PMCC

Lower Limits: 1.4

Upper Limits: 7.5

Extinguishing Media: DRY CHEMICAL, FOAM, CO2.

Fire Fighting Procedures: ALCOHOL FOAM

Unusual Fire/Explosion Hazard: CAN REACT VIGOROUSLY WITH REDUCING MATERIALS.

Accidental Release

Spill Release Procedures: VENTILATE AREA. REMOVE ALL SOURCES OF FLAME, HEAT & SPARKS. WEAR RUBBER GLOVES & USE RAGS OR DISPOSABLE PAPER TOWELS.

Handling

Handling and Storage Precautions: INSIDE STORAGE IN STANDARD FIRE-RESISTIVE FLAMMABLE LIQUIDS STORAGE ROOM OR CABINET.

Exposure Controls

Respiratory Protection: CHEM CARTRIDGE RESPIRATOR OR AIRLINE RESPIRATOR.

Ventilation: LOC/MECH-ADEQUATE TO MINIMIZE VAPORS

Protective Gloves: RUBBER GLOVES

Eye Protection: CHEMICAL GOGGLES

Supplemental Safety and Health

Chemical Properties

HCC: F2

Boiling Pt: B.P. Text: 104F 40C

Vapor Pres: 380

Vapor Density: 3.17

Spec Gravity: 0.98

Evaporation Rate & Reference: BU.ACET. GREATER

Solubility in Water:INSOLUBLE
Appearance and Odor:THIN, RED SYRUP, KETONE ODOR
Percent Volatiles by Volume:84.0

Stability

Stability Indicator/Materials to Avoid:YES
AVOID EXPOSURE TO REDUCING MATERIALS.
Stability Condition to Avoid:AVOID EXPOSURE TO HEAT & OPEN FLAME.

Disposal

Waste Disposal Methods:LANDFILL UNLESS PROHIBITED BY LAW, OTHERWISE
INCINERATE. DO NOT INCINERATE SEALED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.