

## 37038-BLACK

## **MSDS Number**

BFRPR

### **National Stock Number**

8010-00-830-1822

### **Product Name**

37038-BLACK

#### Manufacturer

PRATT AND LAMBERT

## **Product Identification**

Product ID:37038-BLACK MSDS Date:01/01/1985 FSC:8010 NIIN:00-830-1822

NIIN:00-830-1822 MSDS Number: BFRPR

## **Responsible Party**

PRATT & LAMBERT

16116 E 13TH ST

WICHITA, KS 67201

US

Cage: PRATT

## Contractor

PRATT AND LAMBERT INC

2153

CLEVELAND, OH 44101-1027

US

216-566-2902 Cage: 61196

# Ingredients

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 25%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM/300STEL;9394

EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

CYCLOHEXANONE (SARA III)

CAS: 108-94-1

RTECS: GW1050000

Fraction By Weight: 15%

OSHA PELS, 50 PPM



ACGIH TLV: S, 25 PPM; 9293 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 15 - 20%
OSHA PEL200 PPM/150 STEL
ACGIH TLV: 50 PPM; 9293
EPA Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

DOT Report Quantity: 1000 LBS

CAS: 67-63-0

RTECS: NT8050000 Fraction By Weight:

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

#### **Hazards**

Effects of Overexposure: IRRIT OF NOSE, THROAT, EYES & POSS DIZZINESS & NAUSEA. SPRAY MIST CONTN LEAD.

#### First Aid

First Aid:INHAL:REMOVE FR EXPOSR & PROVID FRESH AIR.SPLASH EYES-FLUSH IMMED W/LG AMTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV CONTAM CLOTHING & WASH ALL AFFECT AREA W/WATR.INGEST:DO NOT INDUC VOMITNG.CONSULT A DR . IMMED IN ALL CASES.

### Fire Fighting

Flash Point:21F, -6C

Extinguishing Media:CLASS B EXTING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL FOAM

Fire Fighting Procedures: SELF CONTAINED BR3ATH APPARAT WATER MAY BE INEFECTIVE.

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS.ISOLAT FR HEAT, ELECTR EQPMT SPARKS & OPN FLAME.DO NOT APPLY TO VRY HOT SU

#### **Accidental Release**

Spill Release Procedures: REMOV ALL SOUCES OF IGNIT(FLAMES, HOT SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS.) VENTILAT AREA & AVOID BREATHING VAPORS. REMOV W. INERT ABSORB & NON-SPARKING TOOLS. STEPS MUST BE TAKN TO PREVNT CO NTAM OF GROUND WATR OR STREAMS.

## Handling

Handling and Storage Precautions: DO NOT STORE ABOV 120F STORE LG QUANTITIES IN COMPLIA 2W/OSHA 1910.106.CONTNRS SHDL BE GROUNDED & BONDED TO THE RECEIVING CONTNR.

Other Precautions: DO NOT CUT OR WELD ONEMPTY CONTAINER DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

#### **Exposure Controls**



Respiratory Protection: NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY

WHN SPRAYING IN OUTDR

Ventilation: PROVID GEN DILUT/LOC EXHAUST BENT TO KP CONCENT BELO ACEP

TI

Protective Gloves:SOLVENT,IMPERME

Eye Protection: SAFETY EYEWR

Other Protective Equipment: PROTECTV EQPMT TO PRVNT SKN CONTCT.SE

OSHA,W0

Supplemental Safety and Health

## **Chemical Properties**

HCC:F2

Boiling Pt:B.P. Text:174-321F

Vapor Density:>AIR

Evaporation Rate & Reference: Percent Volatiles by Volume: 68

### Stability

Stability Indicator/Materials to Avoid:YES
AVOID CONTCT W/STRONG ACIDS OR AKALINE MATERIALS.
Stability Condition to Avoid:FIRES, HEAT & HOT SURFACES.
Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE & OXIDES OF CARBON & LEAD.

## **Disposal**

Waste Disposal Methods: DISPOSE IN ACORD W/LOCAL, STATE & FEDERAL REGULATION. INCINERATIN EPA APPRVD FACILITY. DO NOT INCINERAT CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.