

## **MMM-A-121**

### **MSDS Number**

BFSGF

### **National Stock Number**

8040-00-843-3461

### **Product Name**

MMM-A-121

### **Manufacturer**

CLIFTON ADHESIVE INC

### **Product Identification**

Product ID: MMM-A-121  
MSDS Date: 01/01/1987  
FSC: 8040  
NIIN: 00-843-3461  
MSDS Number: BFSGF

### **Responsible Party**

CLIFTON ADHESIVE INC  
39 AVENUE C  
BAYONNE , NJ 07002-3417  
US  
Cage: 79833

### **Contractor**

STEVEN INDUSTRIES  
8  
BAYONNE, NJ 07002-3417  
US  
201-437-6501  
Cage: 33150

### **Ingredients**

METALLIC OXIDES  
Fraction By Weight: 1%

VEHICLE

Fraction By Weight: 11%

SOLVENT

Fraction By Weight: 82%  
ACGIH TLV: 525PPM

TOLUENE (SARA III)

CAS: 108-88-3  
RTECS: XS5250000

Fraction By Weight: 17%  
OSHA PEL200 PPM; Z-2  
ACGIH TLV: S, 50 PPM; 9394  
EPA Report Quantity: 1000 LBS  
DOT Report Quantity: 1000 LBS

HEXANE (N-HEXANE)

CAS: 110-54-3  
RTECS: MN9275000  
Fraction By Weight: 50%  
OSHA PEL500 PPM  
ACGIH TLV: 50 PPM; 9293  
EPA Report Quantity: 1 LB  
DOT Report Quantity: 1 LB

## Hazards

Effects of Overexposure: NARCOSIS AND/OR POSSIBLE HEADACHE OR BRONCHIAL CATARRH

## First Aid

First Aid: FRESH AIR-SEE DR.

## Fire Fighting

Flash Point: 15 F TCC -9C  
Lower Limits: 1.2  
Upper Limits: 1.3  
Extinguishing Media: DRY CHEMICAL, CO\*2, FOAM, TRICHOETHANE  
Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.  
Unusual Fire/Explosion Hazard: KEEP AWAY FROM OPEN FLAME, SPARKS, HOT SURFACES AND OXIDIZERS

## Accidental Release

Spill Release Procedures: WIPE UP

## Handling

Handling and Storage Precautions: DO NOT STORE NEAR HEAT OR IN DIRECT SUNLIGHT. STORE IN SOLVENT STORAGE AREA.

## Exposure Controls

Ventilation: LOCAL EXHAUST  
Protective Gloves: YES  
Eye Protection: SAFETY GLASSES  
Other Protective Equipment: HAND CREAM  
Supplemental Safety and Health  
ACETONE AL315000, 23%, 1000PPM; MEK OS0175000, 10% 200PPM; PHENOLIC RESIN

## Chemical Properties

HCC: F2  
Boiling Pt: B.P. Text: 132 F 55 C  
Vapor Pres: 185  
Vapor Density: 0.75  
Spec Gravity: 0.8  
Appearance and Odor: OFF WHITE, KETONE AND NAPHTHANE ODOR  
Percent Volatiles by Volume: 88

## Stability

Stability Indicator/Materials to Avoid: YES

## **Disposal**

Waste Disposal Methods: SOLVENT DISPOSAL PROCEDURES

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.