

## **SHERWOOD 600 STANDARD LAQUER,T60F10**

### **MSDS Number**

BFVXD

### **National Stock Number**

8010-00-905-5419

### **Product Name**

SHERWOOD 600 STANDARD LAQUER,T60F10

### **Manufacturer**

THE SHERWIN WILLIAMS CO

### **Product Identification**

Product ID:SHERWOOD 600 STANDARD LAQUER,T60F10

MSDS Date:01/01/1987

FSC:8010

NIIN:00-905-5419

MSDS Number: BFVXD

### **Responsible Party**

THE SHERWIN WILLIAMS CO

101 PROSPECT AVE N W

CLEVELAND , OH 44115-1042

US

Cage: 82927

### **Contractor**

THE SHERWIN WILLIAMS COMPANY

CLEVELAND, OH 44115-1042

US

216-566-2917/216-566-2902

Cage: 82927

### **Ingredients**

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 20%.

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

Fraction By Weight: 20%.

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 10 - 20%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 10%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Effects of Overexposure:INHALATION OF HIGH VAPOR  
CONCENTRATIONS-ANESTHETIC, SKIN & UPPER RESIRATORY IRRITANT,  
LIGHTHEADEDNES

## First Aid

First Aid:INHALATION:REMOVE TO FRESH AIR. RESTORE BREATISNG.KEEP WARM &  
QUIET. CALL MD. EYE:IMMEDIATELY FLUSH W/WATER FOR AT LEAST 15 MINS.  
CALL MD. SKIN:WASH THOROUGHLY W/SOAP & WATER.REMOVE CONTAMINATED  
CLOTH ING AND WASH BEFORE REUSE.

## Fire Fighting

Flash Point:25F PMCC

Lower Limits:0.9

Extinguishing Media:CO\*2, DRY CHEMICAL, ALCOHOL FOAM

Fire Fighting Procedures:KEEP CONTANERS ISOLATED FROM HEAT, SPARKS, AND  
OPEN FLAME

Unusual Fire/Explosion Hazard:WATER MAY BE INEFFECTIVE.WATER SHOULD BE  
USED TO KEEP EXPOSED CONTAINERS COOL.

## Accidental Release

Spill Release Procedures:REMOVE ALL SURCES OF IGNITION.VENTILATE AREA

AND REMOVE PRODUCT W/INERT ABSORBENT.

## Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT AND OPEN FLAME. AVOID PROLONGED BREATHING OF VAPOR OR SPRAY MIST.

Other Precautions: USE W/ADEQUATE VENTILATION

## Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATORY PROTECTION IF NECESSARY.

Ventilation: PROVIDE ADEQUATE VENTILATION TO KEEP VAPOR CONC. BELOW TLV/LE

Protective Gloves: FOR Prolonged Use

Eye Protection: REQ W/UNDER FRTD SIDEJ-SH

Other Protective Equipment: LD

Supplemental Safety and Health

PRODUCT ALSO CONTAINS 15% ALIPHATIC HYDROCARBON (MFG SUGGEST TLV OF 100 PPM) AND DENSITY: HEAVIER THAN AIR

## Chemical Properties

HCC: F3

Boiling Pt: B.P. Text: 174 TO 325F

Evaporation Rate & Reference: SLOWER THAN ETHER

Appearance and Odor: CLEAR LIQ; ALCOHOL-AROMATIC ODOR

Percent Volatiles by Volume: 85

## Stability

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: CO\*2, CO

## Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/LOCAL, STATE AND FED CODES. MFG SUGGESTS INCINERATION IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.