

TT-E-508C

MSDS Number

BFXGS

National Stock Number

8010-00-932-3354

Product Name

TT-E-508C

Manufacturer

DURON INC

Product Identification

Product ID:TT-E-508C
MSDS Date:01/01/1987
FSC:8010
NIIN:00-932-3354
MSDS Number: BFXGS

Responsible Party

DURON, INC.
10406 TUCKER ST
BELTSVILLE , MD 20705-2201
US
Cage: LO183

Contractor

DURON, INC.
BELTSVILLE, MD 20705-4600
US
301-937-4600
Cage: LO183

Ingredients

TITANIUMDIOXIDE
RTECS: XR2100000

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

SILICATES

ALKYD RESIN (SOLIDS)

Fraction By Weight: 23.1%

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 27%

ACGIH TLV: 100PPM

Hazards

Effects of Overexposure:IRRIT OF RESPIRATORY.TRACT & EYES.INHALATION OF HIGH VAP CONCENTR MAY HAVE RESULTS RANGING FR DIZZIN

First Aid

First Aid:EYES:FUSH W/WATER FOR 15 MIN-GET MEDICAL ATTENTION.IF OVERCOME BY VAPOR,REMOVE FROM EXPOSED AREA IF BREATHING IS IRREGULAR OR STOPPED,START RESUSCITATION.

Fire Fighting

Flash Point:104 F TCC 40 C

Lower Limits:0.9%

Extinguishing Media:USE CARBON DIOXIDE,DRY CHEMICAL OR FOAM

Fire Fighting Procedures:FIGHT LIKE A GASOLINE FLASH FIRE

Unusual Fire/Explosion Hazard:EXPOSURE TO EXTREME HEAT MAY CAUSE BURSTING OF CLOSED CONTAINERS.

Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES,KEEP PEOPLE AWAY.RECOVER LIQUID ADD ABSORBENT TO SPILL AREA.AVOID BREATHING VAPORS.VENTILATE ENCL SPACES.KEEP PETROLEUM PRODUCTS OUT OF AL PUBLIC SEWER & STREAMS.

Handling

Handling and Storage Precautions:KEEP AWAY FR HEAT,SPARKS, & OPEN FLAME.

Other Precautions:AVOID PROLONGED CONTACT W/SKIN.DO NOT TAKE INTERNALLY.

Exposure Controls

Respiratory Protection:HYDROCARBON OR ORGANIC VAP CANISTERS.SELF CONTAINED APPARATUS ABOVE

Ventilation:LOC EXHAUST-FACE VELOCITY 60 FPM.

Protective Gloves:HYDROCARBON INS

Eye Protection:SAFETY GOGG OR GLASSES

Other Protective Equipment:MUST COMPLY W/SECTION1910.132-135 OSHA STNDS

Supplemental Safety and Health

ADD'TL HAZ.INGRED:DRIERS;ASA NOTE:PIGMENTS WHICH CONSIST OF TITANTIUMDIOXIDE,CALCIUM CARBONATE AND SILICATES COMBINED PERCENTATE OF WGT 48%

Chemical Properties

Vapor Density:HEAV

Spec Gravity:1.37

Appearance and Odor:LIQUID PAINT-MILD ODOR

Percent Volatiles by Volume:48.7

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:STRONG OXIDANTS LIKE LIQUID CHLORINE& CONCENTRATED,OXYG HI

Hazardous Decomposition Products:CARBON MONOXIDE IN THE CASE OF INCOMPLETE COMBUSTION.

Disposal

Waste Disposal Methods:PLACE IN CLOSED DOT APPRVD CONTAINER.RAGS & ABSORBENTMATERIAL SHOULD BE IMMEDIATELY IMMERSSED IN WATER.USE APPRVD LANDFILL IN ACCORDANCE W/LOCAL STATE & FEDERAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.