

# 17038-BLACK

# **MSDS Number**

**BFXWJ** 

### **National Stock Number**

8010-00-935-7078

#### **Product Name**

17038-BLACK

#### Manufacturer

PRATT AND LAMBERT

# **Product Identification**

Product ID:17038-BLACK MSDS Date:01/01/1985 FSC:8010 NIIN:00-935-7078 MSDS Number: BFXWJ

# **Responsible Party**

PRATT & LAMBERT

16116 E 13TH ST

WICHITA, KS 67201

US

Cage: PRATT

#### Contractor

PRATT AND LAMBERT INC

2153

CLEVELAND, OH 44101-1027

US

216-566-2902 Cage: 61196

# **Ingredients**

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3 RTECS: EL6475000

KIECS: EE0475000

Fraction By Weight: 25%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM/300STEL;9394

EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

YCLOHEXANONE

Fraction By Weight: 25%

ACGIH TLV: 50 PPM



CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 15 - 20% OSHA PEL200 PPM/150 STEL ACGIH TLV: 50 PPM; 9293 EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000 Fraction By Weight:

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

MINERAL SPIRITS CAS: 64475-85-0 RTECS: PY8240000 Fraction By Weight:

ACGIH TLV: 500 PPM Hazards

Effects of Overexposure: IRRIT OF NOSE, THROAT, EYES & POSS DIZZINESS 6 NAUSEA.SPRAY MIST CONTN LEAD.

#### First Aid

First Aid: INHAL: REMOV FR EXPOSR & PROVID DRESH AIR. SPLASH EYES-FLUSH IMMED W/LG AMTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV CONTAM CLOTHING & WASH ALL AFFECT AREA W/WATR.INGEST:DO NOT INDUC VOMITNG.CONSULT A DR. IMMED IN ALL CASES.

#### Fire Fighting

Flash Point:21F,-6C

Extinguishing Media: CLASS B EXTING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL **FOAM** 

Fire Fighting Procedures: SELF CONTAINED BREATH APPARAT, WATER MAY BE

INEFECTIVE.

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS. ISOLAT FR HEAT, ELECTR EQPMT SPARKS & OPN FLAME. DO NOT APPLY TO VRY HOT SUR

#### **Accidental Release**

Spill Release Procedures: REMOV ALL SOURCES OF IGNIT(FLAMES, HOT SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS). VENTILAT AREA & AVOID BREATHING VAPORS.REMOV W/INERT ABSORB & NON-SPARKING TOOLS.STEPS MUSR BE TAKN TO PREVNT CON TAM OF GROUND WATR OR STREAMS.

# Handling

Handling and Storage Precautions: DO NOT SOTE ABOV 120F STORE LG QUANTITIES IN COMPLIA W/OSHA 1910.106.CONTNRS SHLD BE GROUND & BONDED TO THE RECEIVING CONTNR.

Other Precautions: DO NOT CUT OR WELD ON EMPTY CONTAINER, DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.



# **Exposure Controls**

Respiratory Protection: NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY

WHN SPRAYING IN OUTDR.

Ventilation: PROVID GEN DILUT/LOC EXHAUST VENT TO KP CONCENT BELO ACEP

TL

Protective Gloves:SOLVENT,IMPERME

Eye Protection:SAFETY EYEWR

Other Protective Equipment: PROTECTV EQPMT TO PRVNT SKN CONTCT.SE

OSHA,29 CFR 1910.1025 Supplemental Safety and Health

### **Chemical Properties**

Boiling Pt:B.P. Text:174-321F

Vapor Density:>AIR

Evaporation Rate & Reference: Percent Volatiles by Volume: 93

# **Stability**

Stability Indicator/Materials to Avoid:YES
AVOID CONTCT W/STRONG ACIDS OR AKALINE MATERIALS
Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES.
Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE & OXIDES OF CARBON & LEAD.

Conditions to Avoid Polymerization: DO NOT ADD DRIERS OR REACTIV CHEM W/O TECHN SUPERVISION.

### **Disposal**

Waste Disposal Methods: DISPOSE IN ACCORD W/LOCAL, STATE & FEDERAL REGULATIONS. INCINERATIN EPA APPRVD FACILITY. DO NOT INCINERAT CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.