

## **FLEXANE 94 LIQUID RESIN**

### **MSDS Number**

BGGSZ

### **National Stock Number**

8030-01-036-9228

### **Product Name**

FLEXANE 94 LIQUID RESIN

### **Manufacturer**

DEVCON

### **Product Identification**

Product ID:FLEXANE 94 LIQUID RESIN

MSDS Date:01/01/1985

FSC:8030

NIIN:01-036-9228

MSDS Number: BGGSZ

### **Responsible Party**

DEVCON

Emergency Phone: (617) 777-1100

Cage: 16059

### **Contractor**

DEVCON CORP

DANVERS, MA 01923-3753

US

1-508-777-1100

Cage: 16059

### **Ingredients**

METHYLENE BIS (4-CYCLOHEXYL)ISOCYANATE SEE SUPP DATA

Fraction By Weight: 15%

ACGIH TLV: C, 0.01 PPM

### **Hazards**

Effects of Overexposure:SKIN: POSS IRRIT,SENSITIZATION. EFFECTS MAY BE DELAYED. EYES: SEVERE IRRIT. INH: IRRIT (SEE SUP DATA

### **First Aid**

First Aid:SKIN: WASH W/ISOPROPYL ALCOHOL OR RUBBING ALCOHOL IF AVAIL. FOLLOW W/PLENTY OF SOAP/WATER. EYES: FLUSH W/WATER AT LEAST 15 MIN. INH: REMOVE PERSON TO FRESH AIR. INGEST: OBTAIN IMMED MEDICAL ATTN. IN A LL CASES OBTAIN MEDICAL ATTN.

### **Fire Fighting**

Flash Point:>400 F TCC

Extinguishing Media:WATER, FOAM, CO\*2, DRY CHEMICAL

Fire Fighting Procedures:WEAR FACE MASK W/AIR SUPPLY. DONT BREATHE FUMES OR SMOKE

Unusual Fire/Explosion Hazard:DURING A FIRE IRRITATING AND/OR TOXIC GASES OR MISTS MAY BE PRESENT

### **Accidental Release**

Spill Release Procedures:PREVENT SKIN & EYE CONTACT. ABSORB SPILLAGE ON INERT COMPOUND & TRANSFER TO AN OPEN CONTAINER IN A WELL VENTILATED

AREA. TREAT W/DILUTE OR HOUSEHOLD AMMONIA FOR 24 HRS BEFORE DISPOSAL. DO NOT SEAL CONTAINERS. WASH SPILL AREA W/HEAVY DUTY DETERGENT.

## Handling

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. PREVENT MATERIAL CONTACT W/WATER OR MOISTURE, MAY RUPTURE CLSD CONTAINERS. DO NOT HEAT, SPRAY OR ATOMIZE LIQUID.

Other Precautions:KEEP HANDS AWAY FROM EYES WHEN HANDLING MATERIAL OR BEFORE WASHING AFTER USE. WASH THOROUGHLY AFTER USING, PARTICULARLY BEFORE EATING OR SMOKING.

## Exposure Controls

Respiratory Protection:NONE NEEDED NORMALLY W/PROPER VENTILATION

Ventilation:ADEQ TO KEEP VAPORS BELOW TLV.

Protective Gloves:CHEM RESIST RUB

Eye Protection:SAFETY GLASSES/SIDE SHLD

Other Protective Equipment:PROTECTIVE CLOTHING AS REQD TO PREVENT SKIN CONTACT

Supplemental Safety and Health

VAPOR PRESSURE: EFFECTS: DRY THROAT, COUGH, OR ASTHMA LIKE SYMPTOMS. KEY1:T4.

## Chemical Properties

HCC:T4

Boiling Pt:B.P. Text:>300F

Spec Gravity:1.04

Evaporation Rate & Reference:NA

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR LIQUID, FAINT ODOR

## Stability

Stability Indicator/Materials to Avoid:YES

H<sub>2</sub>O/MOISTURE CAN CAUSE RUPTURE OF CLOSED CONTNR(PRESSURE)

Hazardous Decomposition Products:FIRE:CO\*2, CO, OXIDES OF NITROGEN, HCN, OTHERS NOT DETERMINE

## Disposal

Waste Disposal Methods:REMOVE TO A WASTE DISPOSAL FACILITY OPERATING IN COMPLIANCE W/ FED, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.