
G/S GRAY, 36081, 03GY187C

MSDS Number

BGKZZ

National Stock Number

8010-01-084-6963

Product Name

G/S GRAY, 36081, 03GY187C

Manufacturer

DEFT INC CHEMICAL COATING DIV

Product Identification

Product ID:G/S GRAY, 36081, 03GY187C

MSDS Date:01/01/1987

FSC:8010

NIIN:01-084-6963

Kit Part:Y

MSDS Number: BGKZZ

Responsible Party

DEFT INC CHEMICAL COATING DIV

17451 VON KARMAN AVE

IRVINE , CA 92714-6205

US

Emergency Phone: 800-424-9300 CHEMTREC

Info Phone: 714-474-0400

Cage: 33461

Contractor

DEFT, INC.

IRVINE, CA 92614

US

949-474-0400

Cage: 33461

Ingredients

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 25%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 15%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

DIBUTYL TIN DILAURATE (AS TIN)

CAS: 77-58-7

RTECS: WH7000000

Fraction By Weight:

OSHA PELs, 0.1 MG/M3

ACGIH TLV: S, 0.1 MG/M3; 8990

Hazards

Effects of Overexposure: INHALATION: HEADACHE/DIZZINESS/STAGGERING
GAIT/CONFUSION/UNCONSCIOUSNESS/COMA. EYE/SKIN: IRRITANT.

First Aid

First Aid: VAPORS: REMOVE TO FRESH AIR. RESTORE BREATHING. KEEP
WARM/QUIET. NOTIFY A PHYSICIAN. EYES: FLUSH W/WATER FOR 15 MINUTES,
TAKE TO A PHYSICIAN FOR MED ATT. SKIN: WASH AFFECTED AREAS W/WATER.
REMOVE CONTAMINATED CLOTHING, CONSULT A PHYSICIAN.

Fire Fighting

Flash Point: 24F (TCC)

Lower Limits: 1.7%

Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures: USE PROTECTIVE EQUIPMENT/SCBA. WATER COOL
CONTAINERS.

Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. CLOSED
CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES/HOT
SURFACES/SPARK SOURCES). AVOID BREATHING VAPORS. CONTAIN AND REMOVE
WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions: WASH HANDS BEFORE EATING/SMOKING OR
USING WASHROOM. SMOKE IN SMOKING AREA ONLY. KEEP CONTAINER UPRIGHT
CLOSE TO PREVENT LEAKAGE.

Other Precautions: DON'T STORE OR USE NEAR HEAT/SPARKS/FLAME. PREVENT
PROLONGED OR REPEATED BREATHING OF VAPOR OR SPRAY MIST. PROLONGED
OVEREXPOSURE CAN CAUSE AN ALLERGIC REACTION.

Exposure Controls

Respiratory Protection: CONFINED AREAS: APPROVED AIR LINE RESPIRATORS OR
HOODS.

Ventilation: VENT FUMES ON HEATING.

Protective Gloves: NEOPRENE/RUBBER

Eye Protection: SAFETY EYEWEAR

Other Protective Equipment: REMOVE/WASH CONTAMINATED CLOTHING BEFORE
REUSE.

Supplemental Safety and Health

MSDS DATE: 04 DEC 85. WT/GAL: 10.15. KEY1: F3.

Chemical Properties

HCC: F5

Boiling Pt: B.P. Text: 168-313F

Vapor Density: >AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 57.9

Stability

Stability Indicator/Materials to Avoid: YES

ACIDS AND BASES

Stability Condition to Avoid: ELEVATED TEMPERATURES

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED LANDFILL FACILITY. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.