

CARB-MEDIC CARBURETOR,PART #M48-14,-24

MSDS Number

BGLBS

National Stock Number

6850-01-085-1423

Product Name

CARB-MEDIC CARBURETOR,PART #M48-14,-24

Manufacturer

RADIATOR SPECIALTY COMPANY

Product Identification

Product ID: CARB-MEDIC CARBURETOR,PART #M48-14,-24

MSDS Date: 01/01/1987

FSC: 6850

NIIN: 01-085-1423

MSDS Number: BGLBS

Responsible Party

RADIATOR SPECIALTY COMPANY

1400 W. INDEPENDENCE BLVD.

CHARLOTTE , NC 28208

US

Emergency Phone: 704-377-6555

Info Phone: 704-377-6555

Cage: 77628

Contractor

RADIATOR SPECIALTY COMPANY

34689

CHARLOTTE, NC 28208

US

704-377-6555/303-623-5716

Cage: 77628

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 50%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 25%
OSHA PELs,200PPM/250STEL
ACGIH TLV: S,200PPM/250STEL; 93
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 25%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure: CAN CAUSE PERM EYE DAMAGE. LIVER OR KIDNEY
DAMAGE ON PROLONGED EXPOSURE. INHAL: IRRITATION (SEE "ADD")

First Aid

First Aid: SKIN: WASH W. SOAP & H₂O. EYES: FLUSH W. H₂O. INGESTED: DON'T
INDUCE VOMITING. INHALED: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF
NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE
ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

Fire Fighting

Flash Point: NONE

Extinguishing Media: USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard: CONTENTS UNDER PRESSURE. AT ELEVATED
TEMP, CONTAINER MAY BURST, MAY RELEASE PHOSGENE & HCL FROM DECOMP.

Accidental Release

Spill Release Procedures: WIPE UP W/ RAGS. OBSERVE HEALTH HAZARD
DESCRIBED; REMOVE IGNITION SOURCES, VENTILATE AREA. CONFINE SPILL &
TRANSFER TO WASTE DRUM.

Handling

Handling and Storage Precautions: STORE AT TEMP BELOW 120F. AWAY FROM
SPARKS, FLAMES, & OXIDIZING AGENTS.

Exposure Controls

Respiratory Protection: FOR BULK HANDLING

Ventilation: LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves: FOR BULK HANDLE

Eye Protection: GOGGLES/FACE SHIELD

Other Protective Equipment: BUNA-N APRON FOR BULK HANDLING.

Supplemental Safety and Health

MSDS DATED SEP, 85. FORMULATION CHANGE FROM PART A.

Chemical Properties

HCC: V3

Boiling Pt: B.P. Text: 105F/40.6C

Spec Gravity: >1.0

Solubility in Water: PARTLY

Appearance and Odor: COLORLESS LIQ W/CHARACTERISTIC ODOR
Percent Volatiles by Volume: 100

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZING AGENTS.
Stability Condition to Avoid: AVOID TEMP > 120F
Hazardous Decomposition Products: CO, PHOSGENE, HYDROCHLORIC ACID.

Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.