

BRACO MICRONIC 882

MSDS Number

BGRKX

National Stock Number

9150-01-256-6433

Product Name

BRACO MICRONIC 882

Manufacturer

CASTROL INC BRAY PRODUCTS DIV

Product Identification

Product ID:BRACO MICRONIC 882

MSDS Date:12/30/1987

FSC:9150

NIIN:01-256-6433

MSDS Number: BGRKX

Responsible Party

CASTROL INC., BRAY PRODUCTS DIV.

16715 VON KARMAN AVE.,SUITE 230

IRVINE , CA 92714

Emergency Phone: 714-660-9414

Info Phone: 714-660-9414 OR 201-980-9100

Preparer: KAREL WRIGHT

Cage: KO960

Contractor

CASTROL INDUSTRIAL NORTH AMERICA INC SPECIALTY PRODUCTS

DOWNERS GROVE, IL 60515-1280

US

630-241-4140

Cage: 2R128

Ingredients

SYNTHETIC HYDROCARBON

OSHA PEL5 MG/CUM(OIL MIST)

ACGIH TLV: 5 MG/CUM STEL 10 MG

TRIPHENYL PHOSPHATE

CAS: 115-86-6

RTECS: TC8400000

Fraction By Weight:

OSHA PEL3 MG/M3

ACGIH TLV: 3 MG/M3; 9192

Hazards

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT MAY CAUSE IRRITATION. VAPORS

MAY IRRITATE RESPIRATORY TRACT. PRODUCT CONTAINS TRI-PHENYL PHOSPHATE WHICH HAS BEEN REPORTED TO INHIBIT CHOLINESTERASE IN HUMANS.

Effects of Overexposure:EYE,SKIN IRRITATION.

Medical Cond Aggravated by Exposure:NONE REPORTED.

First Aid

First Aid:EYE:FLUSH WITH WATER 15 MIN. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP & WATER. INHALED:REMOVE FROM EXPOSURE. INGESTED:DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:COC

Flash Point:430F/221C

Extinguishing Media:DRY CHEMICAL,FOAM,WATER

Fire Fighting Procedures:USE WATER TO COOL FIRE EXPOSED CONTAINERS.

WATER OR FOAM MAY CAUSE FROTHING IF PRODUCT IS OVER 200F/93C.

Unusual Fire/Explosion Hazard:NONE REPORTED

Accidental Release

Spill Release Procedures:ABSORB WITH INERT MATERIAL. STORE IN CLOSED CONTAINERS PENDING DISPOSAL.

Neutralizing Agent:NONE

Handling

Handling and Storage Precautions:STORE TIGHTLY CLOSED IN A COOL,DRY,WELL VENTILATED AREA. KEEP AWAY FROM HEAT & FLAME.

Other Precautions:EMPTY CONTAINERS MAY CONTAIN VAPORS OR RESIDUE. DO NOT CUT,DRILL OR WELD CONTAINERS.

Exposure Controls

Respiratory Protection:USE NIOSH CARTRIDGE OR SUPPLIED AIR RESPIRATOR IF EXPOSED ABOVE TLV.

Ventilation:NORMAL ROOM VENTILATION IS NORMALLY SATISFACTORY. USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:PLASTIC OR RUBBER

Eye Protection:SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment:PLASTIC/RUBBER APRON OR OTHER GARMENTS AS DICTATED BY THE JOB.

Work Hygienic Practices:USE NORMAL CHEMICAL HYGIENE PRACTICE. REMOVE & LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

Chemical Properties

HCC:V6

Boiling Pt:B.P. Text:>500F/260C

Spec Gravity:0.86

Solubility in Water:SLIGHT

Appearance and Odor:BRIGHT RED LIQUID,MILD PETROLEUM ODOR

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NONE REPORTED. ELEVATED TEMPERATURES.

Hazardous Decomposition Products:NORMAL PRODUCTS OF COMBUSTION.

Disposal

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

