

RUST PENETRANT #96560

MSDS Number

BGTNG

National Stock Number

6850-00B030055

Product Name

RUST PENETRANT #96560

Manufacturer

CURTIS INDUSTRIES

Product Identification

Product ID:RUST PENETRANT #96560

MSDS Date:10/08/1985

FSC:6850

NIIN:00B030055

MSDS Number: BGTNG

Responsible Party

CURTIS INDUSTRIES

34999 CURTIS BOULEVARD

EASTLAKE , OH 44094

US

Emergency Phone: 216-951-2400 EXT.5678

Cage: 91636

Contractor

CURTIS INDUSTRIES

EASTLAKE, OH 44094

US

216951-2400 EXT. 282

Cage: 91636

Ingredients

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 12%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAANT; 9192

MINERAL SPIRITS

CAS: 64742-88-7

Fraction By Weight: 18%

ACGIH TLV: 300

KEROSENE

CAS: 8008-20-6

RTECS: OA5500000

Fraction By Weight: 60%

ACGIH TLV: 300

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure:MAY CAUSE DIZZINESS OR EXTREME CASE,ABSENCE OF OXYGEN COULD PRODUCE NORCOSIS.

First Aid

First Aid:IF UNCONSCIOUS,REMOVE PERSON TO FRESH AIR AND CALL A PHYSICIAN.IF SPRAYED IN EYES,FLUSH IMMEDIATELY WITH LARGE QUANTITIES OF WATER.

Fire Fighting

Flash Point Method:TOC

Flash Point:BELOW 20F

Extinguishing Media:WATERFOG,FOAM,CO2 OR DRY CHEMICAL.

Fire Fighting Procedures:KEEP CONTAINERS COOL.USE EQUIPMENT OR SHIELDING REQUIRED TO PROTECT PERSONNEL AGAINST BURSTING OR VENTING CONTAINERS.

Unusual Fire/Explosion Hazard:AT ELEVATED TEMPERATURES(130 OR OVER)CONTAINERS MAY VENT,RUPTURE,OR BURST.

Accidental Release

Spill Release Procedures:FLUSH WITH LARGE QUANTITIES OF WATER.VENTILATE AREA.

Handling

Handling and Storage Precautions:READ AND FOLLOW CAUTIONS ON PRODUCT LABEL.DO NOT STORE IN TEMPERATURES ABOVE 120F.

Exposure Controls

Respiratory Protection:AVOID BREATHING CONCENTRATED VAPORS OR PARTICLES FROM ALL PRODUCTS NOT SPECIFICALLY DESIGNED TO BE INHALED.

Ventilation:NORMAL USE-NORMAL VENTILATION.

Supplemental Safety and Health

Chemical Properties

Vapor Pres:Vapor Density:>THAN AIR

Solubility in Water:LESS THAN 1%

Appearance and Odor:CLEAR-SOLVENT.

Percent Volatiles by Volume:90

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:PRESSURIZED CONTAINERS COULD RUPTURE ABOVE 130F.

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE AND WATER.

Disposal

Waste Disposal Methods:DO NOT PUNCTURE OR INCINERATE CONTAINERS.GIVE TO A DISPOSAL SERVICE EQUIPPED TO SAFELY HANDLE AND DISPOSE OF PRESSURIZED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

