

EPOXY COATING, COMP II, POLYAMID, UO-082

MSDS Number

BGWTB

National Stock Number

8010-00-082-2438

Product Name

EPOXY COATING, COMP II, POLYAMID, UO-082

Manufacturer

CRAWFORD LABORATORIES INC

Product Identification

Product ID:EPOXY COATING, COMP II, POLYAMID, UO-082

MSDS Date:10/20/1987

FSC:8010

NIIN:00-082-2438

Kit Part:Y

MSDS Number: BGWTB

Responsible Party

CRAWFORD LABORATORIES, INC.

4165 SOUTH EMERALD AVENUE

CHICAGO , IL 60609

US

Emergency Phone: 312-433-1307

Info Phone: 312-376-7132

Cage: DO165

Contractor

CRAWFORD LABORATORIES, INC

CHICAGO, IL 60609

US

312-376-7132

Cage: 5V430

Ingredients

ALCOHOL (VAPOR PR MM HG 33)

CAS: 67-63-0

RTECS: AY9900000

Fraction By Weight: 20-50%

ACGIH TLV: 400 PPM

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 20-50%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ALCOHOL

CAS: 67-63-0

RTECS: AY9900000

Fraction By Weight: 5-20%

ACGIH TLV: 400 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:TOXICITY MAY CAUSE HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF CONSCIOUSNESS. EYE IRRITATION, IRRITATED MUCOUS MEMBRANES, VOMITING DUE TO INGESTION, DEFATTING AND DRYING OF THE SKIN MAY RESULT IN IRRITATION AND DERMATITIS. Effects of Overexposure:OVEREXPOSURE MAY PRODUCE VARIOUS EFFECTS-ACUTE TOXICITY, EYE IRRITATION, IRRITATED MUCOUS MEMBRANES, VOMITING, SKIN IRRITATION & DERMATITIS.

Medical Cond Aggravated by Exposure:SEE ABOVE.

First Aid

First Aid:DO NOT INDUCE VOMITING, EYE CONTACT-FLUSH EYES WITH WATER FOR 15 MINUTES. INHALATION-REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF NECESSARY. KEEP VICTIM QUIET. SKIN CONTACT-FLUSH WITH WATER-REMOVE CONTAMINATED CLOTHING, WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IMMEDIATELY.

Fire Fighting

Flash Point Method:SCC

Flash Point:22F/-6C

Lower Limits:2.

Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL.

Fire Fighting Procedures:WATER MAY BE USED TO KEEP EXPOSED CONTAINERS COOL AND TO KEEP FLAMMABLE STRUCTURES WET. DO NOT ENTER FIRE AREA W/O PROPER PROTECTION.

Unusual Fire/Explosion Hazard:SEALED CONTAINERS MAY EXPLODE IF OVERHEATED. WATER PRESSURE MAY SPREAD A FLAMMABLE LIQUID FIRE.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. SOAK UP WITH AN ABSORBENT AND PLACE IN NON-LEAKING CONTAINERS. SEAL TIGHTLY FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:TREAT AS A HAZARDOUS-FLAMMABLE MATERIAL. KNOW APPLICABLE DOT REGULATIONS BEFORE ATTEMPTING TO TRANSPORT THIS MATERIAL.

Exposure Controls

Respiratory Protection:MUST PROVIDE ADEQUATE VENTILATION TO KEEP VAPOR CONCENTRATIONS BELOW ESTABLISHED TLV LIMIT. IN MORE CONFINED AREAS A NIOSH-MSHA APPROVED RESPIRATOR EQUIPPED WITH ORGANIC CARTRIDGE SHOULD BE WORN.

Ventilation:MUST PROVIDE ADEQUATE VENTILATION.

Protective Gloves:RUBBER GLOVES.

Eye Protection:APPROVED SAFETY GOGGLES AND FACE SHIELD.

Other Protective Equipment:HAVE EYE BATH AVAILABLE.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:175-180F

Vapor Density: >AIR
Evaporation Rate & Reference: 2.35 X N-BUTYL ACETATE
Appearance and Odor: CLEAR LIQUID.
Percent Volatiles by Volume: 78.6

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZING AGENTS AND STRONG ALKALIES.
Stability Condition to Avoid: AVOID HEAT, SPARKS, OPEN FLAMES AND
INCOMPATIBILITIES, STRONG OXIDIZING AGENTS AND ALKALIES.
Hazardous Decomposition Products: INCOMPLETE COMBUSTION FOR PRODUCTS
LIKE THIS MAY GENERATE HIGHLY POISONOUS CARBON MONOXIDE AND OTHER
TOXIC GASES.

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH CURRENT LOCAL, STATE
AND FEDERAL REGULATION. CONTACT AN APPROVED DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.