https://msdsreport.com/msds/BGXDV

•

92-92B PENETRANT, FLUORESCENT

MSDS Number

BGXDV

National Stock Number

6850-01-263-9777

Product Name

92-92B PENETRANT, FLUORESCENT

Manufacturer

MET L CHEK COMPANY

Product Identification

Product ID:92-92B PENETRANT,FLUORESCENT MSDS Date:10/15/1986 FSC:6850 NIIN:01-263-9777 MSDS Number: BGXDV

Responsible Party

MET-L-CHEK COMPANY

1639 ECULID STREET

SANTA MONICA , CA 90404-3770

US

Emergency Phone: 213-450-1111

Info Phone: 213-450-1111

Cage: 98733

Contractor

MET-L-CHEK COMPANY

00000

SANTA MONICA, CA 90404

US

310-450-1111/FAX 310452-4046

Cage: 98733

Ingredients

DISTILLATE (PETROLEUM), HYDROTREATED MIDDLE; ON MSDS MFR

CAS: 64742-46-7

RTECS: JN9379645

OSHA PEL5MG/CUM

ACGIH TLV: 5MG/CUM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:MAY CAUSE SLIGHT SKIN IRRITATION;VAPORS OR OIL MIST CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT. Effects of Overexposure:EYES:PRESUMED NON-IRRITATING;SKIN:SLIGHT IRRITATION ON LIQUID CONTACT;INHALATION:VAPORS OR OIL MIST MAY CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT;INGESTION:MAY

RESULT IN VOMITING.



Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND RESPIRATORY DISORDER MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

•

First Aid

First Aid:EYES:FLUSH WITH WATER.GET MEDICAL HELP IF IRRITATION OCCURS OR PERSISTING; SKIN:FLUSH WITH WATER.WASH WITH WATER & SOAP.GET MED ATTN FOR PERSISTING IRRITATION; INHALATION:REMOVE TO FRESH AIR.PROVIDE O XYGEN IF BREATHING IS DIFFICULT GET MEDATTN IF NEEDED; INGESTION:DO NOT INDUCE VOMITING.GET MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:COC Flash Point:210F(98.9C) Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE OR FOAM; DO NOT USE DIRECT STREAM OF WATER. Fire Fighting Procedures:IN CONFINED AREA,DO NOT ENTER WITHOUT A FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:NOT KNOW

Accidental Release

Spill Release Procedures: ELIM IGNITION SOURCES.WEAR APPROPRIATE PROTECTIVE CLOTHING & RESPIRATOR.DIKE & RESPIRATOR.DIKE & TRANSFER LIQ TO A SALVAGE TANK.SOAK UP RESIDUE WITH ABSORBENT CLAY,SAND OR OTHR MATL.PLACE RAGS & ABSOR BED WASTE MATERL IN COVERED NON-LEAKINGCONTAINERS Neutralizing Agent:.

Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT/IGNITION SOURCES. STORE IN DRY,COOL,& VENTILATED LOCATION. DO NOT STORE NEAR OXIDIZING MATERIAL. AVOID PHYSICAL DAMAGE TO CANS. Other Precautions: MINIMIZE SKIN CONTACT.

Exposure Controls

Respiratory Protection:IF EXPOSURE EXCEEDS TVL,USE NIOSH APPRVD RESPIRATOR TO PREVENT OVEREXPOSURE. Ventilation:PER MANUFACTURER,PRIVIDE LOCAL EXHAUST, OR MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TVL. Protective Gloves:CHEMICAL RESISTANT. Eye Protection:GOGGLES Other Protective Equipment:EYE WASH FOUNTAINS AND SAFETY SHOWERS. Work Hygienic Practices:WASH WITH SOAP AND WATER BEFORE EATING, DRINKING,SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health PER QPL-25135-15,THREE PENETRANTS,FP-91C(M)FP-92B & FP-93A(M) ARE QUALIFIED ITEMS FOR NSN OF TYPE I,METHOD C,LEVEL 1 UNDER THE MIL-I-25235,REV D;THE MFR MAY SHIP/SUPLY,ONE OF THESE THREE PENETRANTS UN DER THIS NSN.THIS DATA ENTRY IS OF FP-92B;OTHER TWO PENETRANTS ARE UNDER PNI B & C,THIS NSN.

Chemical Properties

HCC:N1 Boiling Pt:B.P. Text:>400F/>204C Spec Gravity:0.86 Solubility in Water:NEGLIGIBLE Appearance and Odor:YELLOW-GREEN LIQUID.SLIGHT HYDROCARBON ODOR

Stability

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIAL Stability Condition to Avoid:HEAT & IGNITION SOURCES. Hazardous Decomposition Products:XARBON MONOXIDE & OTHER UNIDENTIFIED ORGANIC COMPOUNDS.

Disposal

Waste Disposal Methods: DISPOSE OF AS EPA HAZARDOUS WASTE



#D001,IGNITABLE WASTE.PLACE WASTE MATERIAL IN AN APPROPRIATE DISPOSAL FACILITY, OR DISPOSE OF IN COMPLIANCE WITH FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.