

## **LIQUID POLISH A-A-15**

### **MSDS Number**

BGXNH

### **National Stock Number**

7930-00-721-8873

### **Product Name**

LIQUID POLISH A-A-15

### **Manufacturer**

INDUSTRIAL FLOOR FINISHES

### **Product Identification**

Product ID: LIQUID POLISH A-A-15

MSDS Date: 05/01/1987

FSC: 7930

NIIN: 00-721-8873

MSDS Number: BGXNH

### **Responsible Party**

INDUSTRIAL FLOOR FINISHES

605 SPRING ST

BEDFORD , MA 01730

US

Emergency Phone: 617-667-5161 OR LOCAL POISON CENTER

Info Phone: 617-667-5161

Preparer: T. PITROLFFY

Cage: INDUS

### **Contractor**

INDUSTRIAL FLOOR FINISHES

BEDFORD, MA 01730

US

1-617-667-5161

Cage: INDUS

### **Ingredients**

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 17%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

### **Hazards**

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: ACUTE: PRIMARY EYE & SKIN IRRITANT WITH CONTACT. INHALATION: MAY CAUSE HEADACHE, DIZZINESS & NAUSEA. CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV.

### **First Aid**

First Aid:EYE CONTACT: FLUSH WITH WATER; SKIN: WASH WITH SOAP & WATER, APPLY SKIN CREAM. INHALATION:REMOVE TO FRESH AIR,RESTORE BREATHING,CALL PHYSICIAN. INGESTION:DRINK WATER OR MILK, DO NOT INDUCE VOMITING-CA LL POISON CONTROL.

## Fire Fighting

Flash Point Method:TCC  
Flash Point:MIN 104F  
Lower Limits:0.8  
Upper Limits:6.0  
Extinguishing Media:FOAM-CO2-DRY CHEMICAL.  
Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP OR AUTO-IGNITION.  
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT,CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

## Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION, SPRINKLE WITH ABSORBENT. FOG WITH WATER,FLUSH OR SCRAPE INTO RETAINING AREA OR CONTAINER. INCREASE VENTILATION AVOID BREATHING VAPORS.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS AND OPEN FLAME. USE ADEQUATE VENTILATION.AVOID PROLONGED OR REPEATED CONTACT. KEEP CONTAINER CLOSED.  
Other Precautions:AVOID STATIC BUILD-UP.KEEP AWAY FROM CHILDREN.

## Exposure Controls

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV.  
Ventilation:LOCAL EXHAUST YES MECHANICAL-EXHAUST FROM LOWER LEVELS.  
Protective Gloves:USE RUBBER GLOVES.  
Eye Protection:SAFETY GLASSES.  
Other Protective Equipment:EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM.  
Supplemental Safety and Health  
NONE

## Chemical Properties

Boiling Pt:B.P. Text:215F  
Vapor Pres:2  
Vapor Density:3.8  
Spec Gravity:1.1  
Evaporation Rate & Reference:WATER 0.8  
Solubility in Water:PARTIAL  
Appearance and Odor:GREEN CREAMY LIQUID.  
Percent Volatiles by Volume:74

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS.  
Stability Condition to Avoid:HEAT,SPARKS,OPEN FLAME & FIRE.  
Hazardous Decomposition Products:THERMAL DECOMPOSITION PRODUCES FUMES MAY YIELD CARBON MONOXIDE.

## Disposal

Waste Disposal Methods:INCINERATE OR DISPOSE OF IAW LOCAL,STATE AND FEDEREL REGULATIONS. EMPTY CONTAINERS MAY RETAIN FUMES. DO NOT EXPOSE TO HEAT OR FLAME.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

