

FO 425 A

MSDS Number

BGZZK

National Stock Number

6850-00-274-5421

Product Name

FO 425 A

Manufacturer

FINE ORGANICS CORP

Product Identification

Product ID:FO 425 A MSDS Date: 08/01/1988 FSC:6850 NIIN:00-274-5421 MSDS Number: BGZZK

Responsible Party

FINE ORGANICS CORP

205 MAIN ST

LODI, NJ 07644-0687

US

Emergency Phone: (800) 526-7480

Info Phone: (800) 526-7480 Preparer: J.I. GREENBERG

Cage: 84519

Contractor

FINE ORGANICS CORPORATION

687

LODI, NJ 07644-0687

US

Cage: 84519

Ingredients

HYDROTREATED LIGHT DISTILLATE, PETROLEUM

CAS: 64742-47-8

Fraction By Weight: 100%

OSHA PEL500 PPM ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION: MAY HAVE RESULTS MILD DEPRESSION TO RESPIRATORY IRRITATION. SKIN: PROLONGED CONTACT MAY LEAD TO EXTRACTION OF NATURAL OILS W/RESULTANT IRRITATION. EYE: WILL CAUSE IRRITATION. INGESTION: MA Y AFFECT KIDNEYS. HEALTH RISKS

WHICH VARY FROM PERSON TO PERSON.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INHALATION: MAY HAVE RESULTS MILD DEPRESSION TO



RESPIRATORY IRRITATION. SKIN: PROLONGED CONTACT MAY LEAD TO EXTRACTION OF NATURAL OILS W/RESULTANT IRRITATION. EYE: WILL CAUSE IRRITATION. INGESTION: MAY AFFECT KIDNEYS.

First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE. ADMINISTER ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. EYE: FLUSH W/WATER FOR 15 MIN. INGESTION: DON'T INDUCE VOMITING. GIVE PLENTY OF WATER. IF CONTACTED, REMOV E CONTAMINATED CLOTHES/WASH AREA WITH PLENTY OF WATER. SEEK MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:COC

Flash Point:180F

Extinguishing Media: FOAM, DRY CHEMCIAL, CO2, WATER SPRAY/FOG Fire Fighting Procedures: USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREA. COOL EXPOSED CONTAINRS W/WATER. Unusual Fire/Explosion Hazard: DON'T STORE & MIX WITH STRONG OXIDANTS.

Unusual Fire/Explosion Hazard:DON'T STORE & MIX WITH STRONG OXIDANTS COMBUSTION LIQUID.

Accidental Release

Spill Release Procedures: REMOVE IGNITION SOURCES. RECOVER FREE LIQUID & ADD ABSORBENT TO SPILL AREA. AVOID BREATHING VAPORS. VENTILATE ENCLOSED SPACES.

Exposure Controls

Ventilation:LOCAL EXHAUST: FACE VELOCITY > 60FPM/MECHANICAL: USE

EXPLOSION PROOF EQUIPMENT. Protective Gloves: NEOPRENE Eye Protection: SPLASH GOGGLES Supplemental Safety and Health

Chemical Properties

HCC:V4

Boiling Pt:B.P. Text:401-409F Vapor Pres:Vapor Density:>5

Spec Gravity: 0.79

Evaporation Rate & Reference: (N-BU AC = 1): 0.1

Solubility in Water: NEGLIGIBLE

Appearance and Odor: WATER WHITE-ODORLESS

Percent Volatiles by Volume: 100%

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDANTS LIKE LIQUID CHLORINE, CONCENTRATED OXYGEN SODIUM/CALCIUM HYPOCHLORITE.
Hazardous Decomposition Products:FUMES, SMOKE & CO IN CASE OF INCOMPLETE COMBUSTION.

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/ALL LOCAL, STATE, & FEDERAL REGULATIONS, DISPOSAL RECOMMENDATIONS APPLY TO THE ORIGINAL MATERIAL & ITS CONTAINER, NOT ANY MATERIALS WHICH AREA WASTE BY PRODUCTS OF THE USER' S OPERATION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.