

---

## **KRYLON SPRAY PRIMER; RUDDY BROWN: 1318**

### **MSDS Number**

BHBBB

### **National Stock Number**

8010-00-616-9181

### **Product Name**

KRYLON SPRAY PRIMER; RUDDY BROWN: 1318

### **Manufacturer**

BORDEN INC

### **Product Identification**

Product ID:KRYLON SPRAY PRIMER; RUDDY BROWN: 1318

MSDS Date:06/30/1986

FSC:8010

NIIN:00-616-9181

MSDS Number: BHBBB

### **Responsible Party**

BORDEN, INC

180 EAST BROAD STREET

COLUMBUS , OH 43215

Emergency Phone: (614) 431-6600

Info Phone: (800) 848-9400

Cage: FO346

### **Contractor**

BORDEN, INC

COLUMBUS, OH 43215

US

(614) 431-6600

Cage: FO346

### **Ingredients**

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 33%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 16-17%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight: 1-2%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 23-27%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 4-6%

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9192

## Hazards

Routes of Entry: Inhalation: YES Skin: NO Ingestion: NO

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: INHALATION: CNS DEPRESSION, HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS & ASPHYXIATION, CYANOISIS, RESPIRATORY DISTRESS, DROWSINESS, LIVER & KIDNEY DAMAGE. OVEREXPOSURE W/ PERMANENT BRAIN/N ERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING/INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INHALATION: CNS DEPRESSION, HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS, ASPHYXIATION, CYANOSIS, RESPIRATORY DISTRESS, DROWSINESS, LIVER & KIDNEY DAMAGE, IRRITATION OF NOSE, THROAT, LUNGS, S KIN & EYES.

## First Aid

First Aid: INGESTION: DON'T INDUCE VOMITING, CALL PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL PHYSICIAN. SKIN: FLUSH W/ WATER. EYE: FLUSH W/PLENTRY OF WATER FORAT LEAST 15 MINS. EYELIDS SHOULD BE HELD APART DURING IRRIGATION TO INSURE WATER CONTACT W/ENTIRE SURFACE OF EYES/LIDS. CALL PHYSICIAN.

## Fire Fighting

Flash Point:FLAMMABLE  
Extinguishing Media:USE DRY CHEMICAL, FOAM OR CO2.  
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL. DON'T SPRAY NEAR OPEN FLAME.  
Unusual Fire/Explosion Hazard:EXPOSURE TO HIGH TEMP MAY CAUSE BURSTING.  
AVOID RADIATORS, STOVES, DIRECT SUNLIGHT, OR OTHER HEAT SOURCE.  
DON'T PUNCTURE OR INCINERATE CONTAINER.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL & REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

## Handling

Handling and Storage Precautions:MAY CONTAIN EXPLOSIVE VAPORS. DON'T CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY.  
Other Precautions:DON'T STORE AT TEMPERATURES >120F. AVOID BREATHING VAPOR/MISTS. USE WITH ADEQUATE VENTILATION. AVOID CONTACT W/SKIN & EYES. WASH THOROUGHLY AFTER HANDLING.

## Exposure Controls

Respiratory Protection:AIR CONTAMINANTS CAN EXCEED ACCEPTABLE CRITERIA, USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT.  
Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:IMPERVIOUS  
Eye Protection:GOGGLES  
Work Hygienic Practices:GOOD INDUSTRIAL HYGIENE & SAFETY PRACTICES.  
WASH THOROUGHLY AFTER HANDLING.  
Supplemental Safety and Health

## Chemical Properties

HCC:V3  
Vapor Pres:60  
Vapor Density:>AIR  
Spec Gravity:Evaporation Rate & Reference:FASTER THAN BU AC  
Solubility in Water:SLIGHT  
Percent Volatiles by Volume:80-83%

## Stability

Stability Indicator/Materials to Avoid:YES  
Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE & FEDERAL REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.