https://msdsreport.com/msds/BHBCN

# **STATIC CONDITIONER**

## **MSDS Number**

BHBCN

## **National Stock Number**

8030-01-046-5065

#### **Product Name**

STATIC CONDITIONER

#### Manufacturer

DEXTER CORP

# **Product Identification**

Product ID:STATIC CONDITIONER MSDS Date:10/03/1987 FSC:8030 NIIN:01-046-5065 MSDS Number: BHBCN

## **Responsible Party**

DEXTER CORPORATION

31500 HAYMAN

HAYWARD , CA 94544

Emergency Phone: (415) 471-7171

Info Phone: (415) 796-4972

Preparer: S. MORRIS

Cage: 79436

## Contractor

DEXTER CORP DEXTER ELECTRONIC MATERIALS

INDUSTRY, CA 91746-1282

US

626-968-6511

Cage: 79436

## Ingredients

HYDROTREATED LIGHT DISTILLATE, PETROLEUM

CAS: 64742-47-8

Fraction By Weight: 20-30%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: RESPIRATORY TRACT IRRITATION, HEADACHE, DIZZINESS & DROWSINESS. SKIN/EYE: IRRITATION. Explanation of Carcinogenicity:NONE Effects of Overexposure:INHALATION: RESPIRATORY TRACT IRRITATION, HEADACHE, DIZZINESS & DROWSINESS. SKIN/EYE: IRRITATION,

# **First Aid**

First Aid:INHALATION: REMOVE FROM EXPOSURE. EYE: FLUSH IMMEDIATELY W/LARGE AMOUNTS OF RUNNING WATER FOR AT LEAST 15 MINUTES. SKIN:



WASH W/SOAP & WATER. REMOVE/WASH CONTAMINATED CLOTHING. INGESTION: DRINK WATER.

•

## **Fire Fighting**

Flash Point Method:SCC Flash Point:102F Lower Limits:1.0% Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL, CO2

#### **Accidental Release**

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS, VENTILATE AREA & REMOVE W/INERT ABSORBANT & NON-SPARKING TOOLS.

#### Handling

Handling and Storage Precautions:CONTAINER SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF FEW INCHES. KEEP CONTAINERS CLOSED WHEN NOT IN USE. Other Precautions:MAKE SURE THE DRUM IS COMPLETELY EMPTY BEFORE ATTEMPTING TO WELD/BRAZE. DRUM SHOULD BE INDUSTRIALLY CLEANED PRIOR TO REUSE. DON'T FLAME CUT/BRAZE/WELD W/O A NIOSH APPROVED RESPIRATOR/APPROPRIATE VENTI LATION. DON'T TAKE INTERNALLY.

## **Exposure Controls**

Respiratory Protection:USE NIOSH/MSHA APPROVED AIR LINE TYPE RESPIRATORS/HOODS FOR ENCLOSED & CONFINED AREAS. AIR PURIFYING RESPIRATORS MAY BE USED FOR OTHER AREAS. Ventilation:PROVIDE MECHANICAL/LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:RESISTANT Eye Protection:SAFETY EYEWEAR Work Hygienic Practices:REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health WT PER GAL: 2.957 LBS.

#### **Chemical Properties**

Vapor Density:>AIR

#### Stability

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:CO & OXIDES OF NITROGEN. MAY PRODUCE HAZARDOUS FUMES WHEN HEATED.

#### Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.