

# **GRAY 36375**

### **MSDS Number**

**BHBCQ** 

#### **National Stock Number**

8010-01-067-1139

#### **Product Name**

**GRAY 36375** 

#### Manufacturer

NATIONAL AEROSOL PRODUCTS CO

### **Product Identification**

Product ID:GRAY 36375 MSDS Date:01/01/1987 FSC:8010 NIIN:01-067-1139 MSDS Number: BHBCQ

# **Responsible Party**

NATIONAL AEROSOL PRODUCTS CO.

2193 E. 14TH STREET

LOS ANGELES , CA 90021

Emergency Phone: (213) 627-2668

Info Phone: (213) 627-2668

Cage: 59986

Contractor

NATIONAL AEROSOL PRODUCTS CO SUB OF GROW GROUP INC

LOS ANGELES, CA 90021-2843

US

Cage: 59986

# **Ingredients**

VINYL TOLUENE ALKYD

Fraction By Weight:

**PIGMENT** 

Fraction By Weight:

BINDERS, TYPE UNSPECIFIED

Fraction By Weight:

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100)

CAS: 64742-88-7

Fraction By Weight: 26%

OSHA PEL500 PPM ACGIH TLV: 100 PPM

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000



Fraction By Weight: 34%

OSHA PEL500 PPM/C,1000; Z2 ACGIH TLV: 50 PPM, A2; 9192 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

**PROPANE** 

CAS: 74-98-6

RTECS: TX2275000 Fraction By Weight: OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIANT; 9192

**ISOBUTANE** 

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight:

OSHA PEL1800 MG/CUM ACGIH TLV: 1000 PPM

#### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INGESTION: NAUSEA. EYES: IRRITATION.

INHALATION: ANESTHETIC. SKIN: MINOR IRRITATION.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INGESTION: NAUSEA. EYES: IRRITATION.

INHALATION: ANESTHETIC. SKIN: MINOR IRRITATION.

#### First Aid

First Aid:INGESTION: DON'T INDUCE VOMITING. GET IMMEDIATE MED ATT. EYES: FLUSH W/WATER FOR 5 MINUTES. INHALATION: REMOVE TO FRESH AIR. CALL PHYSICIAN. GIVE MOUTH-TO-MOUTH RESUCITATION IF BREATHING STOPS. SKIN: WASH W/WATER. SEEK MEDICAL HELP.

#### Fire Fighting

Flash Point:Extinguishing Media:WATER FOG, FOAM, CO2, DRY CHEMICAL, HALON Fire Fighting Procedures:USE EQUIPMENT/SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING/WELDING CONTAINERS.

Unusual Fire/Explosion Hazard:DON'T USE NEAR OPEN FLAME, FIRE/WHILE SMOKING. TEMPERATURES >120F MAY CAUSE BURSTING/VENTING. KEEP CONTAINERS COOL.

### **Accidental Release**

Spill Release Procedures: MOP UP, SOAK UP/WIPE UP IMMEDIATELY. PROVIDE VENTILATION. DISPOSE.

# Handling

Handling and Storage Precautions: DON'T STORE WHERE TEMPERATURE IS >120F.

# **Exposure Controls**

Respiratory Protection: ADEQUATE VENTILATION IS REQUIRED. Ventilation: PROVICE ADEQUATE LOCAL EXHAUST VENTILATION. Protective Gloves: REQUIRED FOR PROLONGED CONTACT



Eye Protection: RESISTANT

Other Protective Equipment: NORMAL PROTECTIVE CLOTHING.

Supplemental Safety and Health

## **Chemical Properties**

Vapor Pres:40-50 Vapor Density:>AIR Spec Gravity:0.976 Solubility in Water:SLIGHT

Appearance and Odor:PAINT/SOLVENT ODOR

#### **Stability**

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:OPEN FLAME, FIRE/SMOKING.

### **Disposal**

Waste Disposal Methods: DON'T PUNCTURE/INCINERATE EMPTY/FULL CANS. ONCE SPILLS/LEAKS ARE CLEANED UP, DISPOSE OF WASTE IN ACCORDANCE W/GOVERNMENTAL ORDINANCES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.