

ADHESIVE/SEALANT 262

MSDS Number

BHBDL

National Stock Number

8030-01-142-3131

Product Name

ADHESIVE/SEALANT 262

Manufacturer

LOCTITE CORP

Product Identification

Product ID:ADHESIVE/SEALANT 262

MSDS Date:01/01/1989

FSC:8030

NIIN:01-142-3131

MSDS Number: BHBDL

Responsible Party

LOCTITE CORPORATION

705 NORTH MOUNTAIN ROAD

NEWINGTON , CT 06111

Emergency Phone: (203) 278-1280

Info Phone: (203) 278-1280

Preparer: STEPHEN REPETTO

Cage: 05972

Contractor

LOCTITE CORPORATION

ROCKY HILL, CT 06067-3910

US

860-571-5100

Cage: 05972

Ingredients

POLYGLYCOL DIMETHACRYLATES

Fraction By Weight: 70-75%

BIS-PHENOL A FUMARATE RESINS

Fraction By Weight: 15-20%

POLYETHYLENE, POLYETHYLENE RESIN

CAS: 9002-88-4

RTECS: TQ3325000

Fraction By Weight: 2-3%

SACCHARIN (SARA III)

CAS: 81-07-2

RTECS: DE4200000

Fraction By Weight:

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

1-METHYL-1-PHENYLETHYL HYDROPEROXIDE (CUMENE HYDROPEROXIDE)

CAS: 80-15-9

RTECS: MX2450000

Fraction By Weight:

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

SILICA, CRYSTALLINE - FUSED

CAS: 60676-86-0

RTECS: VV7328000

Fraction By Weight:

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

N,N-DIALKYL TOLUIDINES

Fraction By Weight:

Hazards

LD50 LC50 Mixture: ORAL TOXICITY LD50 = >5000 MG/KG

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: MAY CAUSE DERMATITIS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: MAY CAUSE DERMATITIS.

Medical Cond Aggravated by Exposure:SILICON DIOXIDE DUST HAS BEEN SHOWN
TO CAUSE PULMONARY EFFECTS.

First Aid

First Aid:INGESTION: DON'T INDUCE VOMITING. KEEP INDIVIDUAL CALM.
OBTAIN MEDICAL ATTENTION. INHALATION: DOESN'T APPLY. SKIN/EYE:
FLUSH WITH WATER.

Fire Fighting

Flash Point Method:TCC

Flash Point:>200F

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:SOAK UP AN INERT ABSORBENT. STORE IN PARTLY
FILLED, CLOSED CONTAINER UNTIL DISPOSAL.

Handling

Handling and Storage Precautions:STORE AVOID PROLONGED SKIN CONTACT.

Exposure Controls

Ventilation:NOT NORMALLY NECESSARY
Protective Gloves:RUBBER, PLASTIC RECOMMENDED
Eye Protection:SAFETY GLASSES RECOMMENDED
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:>300F
Vapor Pres:Spec Gravity:1.05
Solubility in Water:SLIGHT
Appearance and Odor:RED LIQUID; MILD ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
NONE
Hazardous Decomposition Products:IRRITATING ORGANIC VAPORS.

Disposal

Waste Disposal Methods:BURY OR INCINERATE IN ACCORDANCE WITH EPA & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.