# EA 937.2 PART B

## MSDS Number

BHBDY

## National Stock Number

5330-01-236-7363

## Product Name

EA 937.2 PART B

## Manufacturer

DEXTER CORP

## Product Identification

Product ID:EA 937.2 PART B
MSDS Date:10/21/1987
FSC:5330
NIIN:01-236-7363
MSDS Number: BHBDY

## Responsible Party

DEXTER CORPORATION

2850 WILLOW PASS ROAD

PITTSBURG , CA 94565

Emergency Phone: (415) 687-4201

Info Phone: (415) 687-4201

Cage: 79436

## Contractor

DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

312

BAY POINT, CA 94565-3299

US

202-483-7616

Cage: 33564

## Ingredients

ISOPROPYL PHENYLENEDIAMINE

CAS: 31626-02-5

Fraction By Weight: 60%

M-PHENYLENEDIAMINE

CAS: 108-45-2

RTECS: SS7700000

Fraction By Weight: 40%

ACGIH TLV: 0.1 MG/M3; 9192

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/SKIN: CAN CAUSE CHEMICAL BURNS.
INHALATION: IRRITATING & CHEST DISCOMFORT & BRONCHITIS. INGESTION:

MODERATELY TOXIC.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES/SKIN: CAN CAUSE CHEMICAL BURNS. INHALATION: IRRITATING & CHEST DISCOMFORT & BRONCHITIS. INGESTION: MODERATELY TOXIC.

## First Aid

First Aid:EYE: FLUSH W/WATER IMMEDIATELY 15 MINS. SKIN: FLUSH W/WATER. THEN WASH THOROUGHLY W/SOAP & WATER. INGESTION: GIVE WATER/MILK IF SWALLOWED. DON'T INDUCED VOMITING.

## Fire Fighting

Flash Point:>300F
Extinguishing Media:DRY CHEMICAL/HALON FIRE EXTINGUISHER/WATER SPRAY, FOAM/FOG.
Fire Fighting Procedures:USE SCBA WHEN FIGHTING FIRES IN CONFINED AREAS.
Unusual Fire/Explosion Hazard:DENSE SMOKE & TOXIC GASES MAY BE LIBERATED.

## Accidental Release

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES & SAFETY GLASSES. COVER W/ ABSORBENT MATERIAL, THEN SCRAPE UP & TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE W/SOLVENT OBSERVING SOLVENT FLAMMABILITY CAUTION S/USE DETERGENT.

## Handling

Handling and Storage Precautions:KEEP PRODUCT COOL IN ACCORDANCE W/LABEL INSTRUCTIONS.

## Exposure Controls

Respiratory Protection:NOT REQUIRED W/INDUSTRIAL VENTILATION.
Ventilation:LOCAL EXHAUST: RECOMMENDED
Protective Gloves:IMPERVIOUS PLASTIC/RUBBER
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:AS NEEDED TO PROTECT SKIN & CLOTHING
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:300F
Spec Gravity:1.15
Solubility in Water:SLIGHTLY
Appearance and Odor:REDDISH BLACK LIQUID W/SLIGHT ODOR

## Stability

STRONG OXIDIZING AGENTS, STRONG LEWIS/MINERAL ACIDS.
Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS & UNDETERMINED ORGANICS .
Conditions to Avoid Polymerization:MIXING RESIN & CURING AGENTS IN BATCHES GREATER THAN ONE POUND TOTAL. DON'T HEAT MIXED ADHESIVE >150F UNLESS CURING.

## Disposal

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO D.O.T. HAZARD CLASS. IF NOT REGULATED BY D.O.T. DISPOSE OF AS ORM-E, DISPOSAL METHOD CAN BE LAND BURIAL/CHEMICAL INCINERATION AS REGULATED BY ALL GOVERNMENTA L AGENCIES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

msdsreport
your source for safety

https://msdsreport.com/msds/BHBDY