

TERRAZO SEALER C

MSDS Number

BHBFV

National Stock Number

8030-00-007-8333

Product Name

TERRAZO SEALER C

Manufacturer

OMEGA CHEMICAL CORP

Product Identification

Product ID:TERRAZO SEALER C

MSDS Date:10/01/1988

FSC:8030

NIIN:00-007-8333

MSDS Number: BHBFV

Responsible Party

OMEGA CHEMICAL CORPORATION

6935 W. 62ND STREET

CHICAGO , IL 60638

US

Emergency Phone: (312) 586-8000

Info Phone: (312) 586-8000

Cage: OB5U9

Contractor

OMEGA CHEMICAL PROD GP, FINE ORGANICS CORP

CHICAGO, IL 60638

US

312-586-8000, 800-424-9300

Cage: OB5U9

Ingredients

NONE AS DEFINED BY 29 CFR 1910.1200 (C) AND FED STD 313C.

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Explanation of Carcinogenicity:NOTE: CONTAINS FORMALDEHYDE (LESS THAN 0.095%)

Effects of Overexposure:INHAL:VAPOR OR MIST CAN CAUSE HEADACHE,NAUSEA,AND IRRITATION OF THE NOSE, THROAT AND LUNGS. SKIN:IRRITATING TO SKIN UPON REPEATED/PROLONG CONTACT. EYE:MILDLY IRRITATING TO EYES.

First Aid

First Aid:INHALATION:MOVE SUBJECT TO FRESH AIR. EYE:FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SEE PHYSICIAN IF IRRITATION PERSISTS. SKIN:WASH SKIN WITH SOAP AND WATER. INGESTION: DILUTE BY GIVI NG 2 GLASSES OF WATER. CALL PHYSICIAN.

Fire Fighting

Flash Point:NONE

Fire Fighting Procedures:NONE SPECIAL. WEAR SELF CONTAINED BREATHING APPARATUS (PRESSURE DEMAND, MSHA/NIOSH APPROVED OR EQUIVALENT AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:MATERIAL CAN BOIL AND SPLATTER ABOVE 212F. POLYMER FILM CAN BURN.

Accidental Release

Spill Release Procedures:FLOORS MAY BE SLIPPERY; USE CARE IN AVOID FALLING. DIKE AND CONTAIN WITH INERT MATERIAL (I.E., SAND,EARTH).TRANSFER LIQUID FOR RECOVERY OR DISPOSAL AND SOLID DIKING MATL TO SEPARATE CONTAINER FOR DISP OSAL. KEEP SPILLS AND RUNOFF FROM SEWERS AND WATER

Handling

Handling and Storage Precautions:STORAGE TEMP MAX 120F (49C) MIN 34F (1C) KEEP FROM FREEZING PRODUCT MAY COAGULATE.

Exposure Controls

Respiratory Protection:NOT NECESSARY UNDER NORMAL USEAGE-RECOMMENDED.

Ventilation:RECOMMENDED.

Protective Gloves:IMPERVIOUS.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Work Hygienic Practices:NO SPECIAL REQUIREMENT.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212F/100C

Melt/Freeze Pt:M.P/F.P Text:32F (O.C)

Vapor Pres:15-20

Vapor Density:Spec Gravity:1.0-1.1

Evaporation Rate & Reference:Solubility in Water:DILUTABLE

Appearance and Odor:MILKY WHITE LIQUID, SLIGHT AMMONIACAL ODOR PH

9.0-10.0

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:DECOMPOSITION IS DEPENDENT ON TIME AND TEMPERATURE. ONSET OF DECOMPOSITION IS 350F (177C).

Disposal

Waste Disposal Methods:COAGULATE THE EMULSION BY THE STEPWISE ADDITION OF FERRIC CHLORIDE AND LIME TO SEPARATE LIQUID FROM SOLID DISPOSE OF BOTH IN ACCORDANCE WITH STATE,LOCAL, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.