## **KAOGUN BF RFT**

## **MSDS Number**

BHBKZ

# **National Stock Number**

5640-00F003295

## **Product Name**

KAOGUN BF RFT

#### Manufacturer

BABCOCK AND WILCOX INSULATING PRODUCTS DIV

## **Product Identification**

Product ID: KAOGUN BF RFT MSDS Date: 01/05/1987 FSC:5640 NIIN:00F003295

MSDS Number: BHBKZ

# **Responsible Party**

BABCOCK & WILCOX, INSULATING PRODUCTS DIVISION

2102 OLD SAVANNAH ROAD

AUGUSTA, GA 30903

Emergency Phone: (404) 796-4200

Info Phone: (404) 796-4200

Cage: 19740 **Contractor** 

# **BABCOCK & WILCOX**

AUGUSTA, GA 30903

(404) 796-4200 Cage: 19740

## **Ingredients**

PARTICULATES NOT OTHERWISE REGULATED (NUISANCE DUST)

Fraction By Weight: >80%

OSHA PEL15 MG/M3 TOTAL DUST ACGIH TLV: 10 MG/M3 TDUST; 8990

SILICA, CRYSTALLINE - CRISTOBALITE

CAS: 14464-46-1 RTECS: VV7325000

Fraction By Weight: 0-15%

**OSHA PELSEE TABLE Z3** 

ACGIH TLV: 0.05 MG/M3 RDUST9293

SILICA, CRYSTALLINE - FUSED

CAS: 60676-86-0 RTECS: VV7328000



Fraction By Weight: 0-15% OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

#### Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: MAY CAUSE DELAYED LUNG INJRY (SILICOSIS). EYES/SKIN: MAY CAUSE TEMPORARY IRRITATION.

Evaluation of Carsing anicity NONE

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INHALATION. NUSIANCE DUST CAUSE NASAL. THROAT/LUNG IRRITATION/DISCOMFORT MAY AGGRAVATE BRONCHIAL.

Medical Cond Aggravated by Exposure:NO

#### First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. INGESTION: DRINK PLENTY OF WATER. SKIN: WASH W/MILD SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER. IF IRRITATION PLERSISTS, CALL A PHYSICIAN.

## **Accidental Release**

Spill Release Procedures: FOLLOW ROUTINE HOUSEKEEPING PROCEDURES. COLLECT SPILLED PRODUCT IN CLOSED CONTAINER.

## Handling

Handling and Storage Precautions: REMOVAL OF THIS PRODUCT AFTER USE MAY RESULT IN THE GENERATION OF DUST.

Other Precautions: REPEATED INHALATION OF RESPIRABLE FREE CRYSTALLINE SILICA DUST MAY CAUSE DELAYED LUNG INJURY (SILICOSIS).

## **Exposure Controls**

Respiratory Protection: FULL FACEPIECE RESPIRATOR W/APPROPRIATE FILTER

PAD OR CARTRIDGE(S)

Ventilation:LOCAL EXHAUST AND MECHANICAL

Protective Gloves: RECOMMENDED

Eye Protection: GOGGLES/SAFETY GLASSES

Other Protective Equipment: AS REQUIRED TO MEET APPLICABLE OSHA

STANDARDS.

Supplemental Safety and Health

## **Chemical Properties**

Spec Gravity: 0.9-3.1

Solubility in Water: INSOLUBLE

Appearance and Odor: COARSE AGGREGATE W/FINE POWDERED MATRIX.

### Stability

Stability Indicator/Materials to Avoid:YES

### Disposal

Waste Disposal Methods: WASTES ARE NOT HAZARDOUS WASTES AS DEFINED BY RCRA (40 CFR 261). COMPLY W/FEDERAL, STATE & LOCAL REGULATIONS. METHOD OF DISPOSAL IS LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.