

## **B54R15 DECK RED, INDUSTRIAL ENAMEL**

### **MSDS Number**

BHBMB

### **National Stock Number**

8010-00F007112

### **Product Name**

B54R15 DECK RED, INDUSTRIAL ENAMEL

### **Manufacturer**

SHERWIN WILLIAMS COMPANY

### **Product Identification**

Product ID: B54R15 DECK RED, INDUSTRIAL ENAMEL

MSDS Date: 01/01/1991

FSC: 8010

NIIN: 00F007112

MSDS Number: BHBMB

### **Responsible Party**

SHERWIN-WILLIAMS COMPANY

101 PROSPECT AVENUE N.W.

CLEVELAND , OH 44115

US

Emergency Phone: 216-556-2917

Info Phone: 216-556-2902

Cage: 54636

### **Contractor**

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

### **Ingredients**

CALCIUM CARBONATE

CAS: 471-34-1

RTECS: FF9335000

Fraction By Weight: 9%

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

ACGIH TLV: C 50 PPM,VAPOR; 9394

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 1%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9394

VOLATILE ORGANIC COMPOUNDS = 3.77 LBS/GAL

RTECS: 9999999VO

Fraction By Weight: 3.77%LB/

ALIPHATIC HYDROCARBON (ALIPHATIC PETROLEUM SOLVENT)

CAS: 64742-47-8

Fraction By Weight: 42%

OSHA PEL400 PPM

ACGIH TLV: 100 PPM

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-IRRITATION OF EYES, SKIN & RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME EXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY IN DEATH. CHRONIC-MAY CAUSE DAMAGE TO LIVER, KIDNE Y, BLOOD FORMING AND REPRODUCTIVE SYSTEM.

Explanation of Carcinogenicity:RATS EXPOSED TO TITANIUM DIOXIDE DUST 250 MG/M3 DEVELOPED CANCER.

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA/LOSS OF COORDINATION ARE INDICATIONS OF EXPOSURE TO VAPORS/SPRAY MISTS. SKIN/ EYE: REDNESS/ITCHING/BURNING SENSATION. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS CAUSES PER MANENT BRAIN/NERVOUS SYSTEM DAMAGE/ADVERSE AFFECTS TO THE LIVER, URINARY, & REPRODUCTIVE SYSTEMS.

Medical Cond Aggravated by Exposure:ALLERGIC SKIN REACTION

## First Aid

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED.

EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN

CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS

PERSIS T. INGESTION:DO NOT INDUCE VOMITING, DRINK 1-2 GLASSES OF WATER. GET MEDICAL HELP IMMEDIATELY.

## Fire Fighting

Flash Point Method:PMCC

Flash Point:101F,38C

Lower Limits:1.0%

Upper Limits:6.0

Extinguishing Media:CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR PROTECTIVE CLOTHING AND SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, & OPEN FLAME. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA & REMOVE WITH INERT ABSORBENT.

---

## Handling

Handling and Storage Precautions:STORE IN A COOL, WELL VENTILATED AREA, AWAY FROM OPEN FLAMES AND SOURCES OF IGNITION.  
Other Precautions:KEEP OUT OF THE REACH OF CHILDREN. USE IN A WELL VENTILATED AREA. AVOID INHALATION OF VAPORS/MIST. WEAR DUST MASK IF SANDING OR SCRAPING DRY PAINT. AVOID INHALING DUST.

## Exposure Controls

Respiratory Protection:IF PERSONAL EXPOSURE CAN'T BE CONTROLLED VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST MATERIALS.  
Ventilation:LOCAL EXHAUST: PREFERABLE. MECHANICAL: ACCEPTABLE IF EXPOSURE TO KEEP Protective Gloves:RECOMMENDED  
Eye Protection:SPECTACLES W/UNPERFORATED SIDESHIELDS  
Other Protective Equipment:USE OF BARRIER CREAM  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT SMOKE WHILE USING PROD  
Supplemental Safety and Health  
WHEN SANDING OR ABRADING THE DRIED FILM, WEAR A DUST MASK/RESPIRATOR. THIS COATING MAY CONTAIN MATERIALS CLASSIFIED AS NUISANCE PARTICULATES/DUST.

## Chemical Properties

HCC:F4  
Boiling Pt:B.P. Text:284F,140C  
Vapor Density:>AIR  
Spec Gravity:0.96-1.14  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Appearance and Odor:RED PAINT  
Percent Volatiles by Volume:>40

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME, ELECTRICAL EQUIPMENT, & HOT SURFACES.  
Hazardous Decomposition Products:CARBON MONOXIDE AND DIOXIDE, AND METAL OXIDES

## Disposal

Waste Disposal Methods:WASTE FROM THIS PRODUCT MAY BE HAZARDOUS AS DEFINED UNDER THE RCRA. INCINERATE IN APPROVED FACILITY. DON'T INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATION S REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.