

SG 404 GREEN GLITTER

MSDS Number

BHBMM

National Stock Number

8010-00F008541

Product Name

SG 404 GREEN GLITTER

Manufacturer

PACTRA COATINGS INC

Product Identification

Product ID:SG 404 GREEN GLITTER

MSDS Date:11/05/1987

FSC:8010

NIIN:00F008541

MSDS Number: BHBMM

Responsible Party

PACTRA COATINGS, INC.

420 S. 11TH AVENUE

UPLAND , CA 91786

Emergency Phone: (714) 946-3871

Info Phone: (714) 946-3871

Cage: FO350

Contractor

PACTRA INDUSTRIES

280

UPLAND, CA 91786-6828

US

(714) 946-3871

Cage: 33777

Ingredients

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 35-40%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

Fraction By Weight: 10-15%

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)

CAS: 123-42-2

RTECS: SA9100000

Fraction By Weight: 5-10%

OSHA PEL50 PPM

ACGIH TLV: 50 PPM; 9192

ETHYL ACETATE (SARA III)

CAS: 141-78-6

RTECS: AH5425000

Fraction By Weight: 5-10%

OSHA PEL400 PPM

ACGIH TLV: 400 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: CAN CAUSE NASAL & RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS & ASPHYXIATION. EYE: SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA. SKIN: IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN DAMAE/NERVOUS SYSTEM DAMAGE. SEVERE OVEREXPOSURE IN LABORATORY ANIMALS HAS CAUSED LIVER ABNORMALITIES/DAMAGE TO KIDNEYS, LUNGS & SPLEEN. INTENTIONAL MISUSE B Y DELIBERATELY CONCENTRATING & INHALINGTHE CONTENTS MAY BE HARMFUL OR FATAL.

Medical Cond Aggravated by Exposure:CAN CAUSE ALLERGIC RESPIRATORY & SKIN REACTION.

First Aid

First Aid:INHALATION: MOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING IS STOPPED, GIVE ARTIFICIAL RESPIRATION & GET MED ATT. EYES: FLUSH W/WATER FOR 15 MINUTES WHILE OCCASIONALLY H OLDING EYELIDS OPEN. GET MED ATT. INGESTION: DON'T INDUCE VOMITING. KEEP PERSON WARM, QUIET, & GET MED ATT/POISON CONTROL CENTER. SKIN: WASH W/SOAP & WATER/HAND CLEANERS. WASH CLOTHING BEFORE REUSE.

Fire Fighting

Flash Point:0F

Lower Limits:1.0%

Extinguishing Media:"ALCOHOL" FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:USE WATER TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP/POSSIBLE AUTOIGNITION/EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF FOG NOZZLES ARE PREFERABLE. USE SCBA.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE/AUTOIGNITE WHEN EXPOSED TO EXTREME HEAT. VAPORS ARE >AIR/MAY TRAVEL ALONG GROUND/MAY BE MOVED BY VENTILATION/IGNITED BY FLAMES.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. VENTILATE AREA. ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL & TRANSFER TO A CLOSED CONTAINER.

Handling

Handling and Storage Precautions:DON'T STORE IN AREAS >120F, IN DIRECT SUNLIGHT, OR NEAR HEAT OR OPEN FLAMES. DON'T PUNCTURE OR INCINERATE.

Other Precautions:STORE LARGE QUANTITIES IN BUILDINGS PROTECTED FOR STORAGE OF NEPA CLASS IC FLAMMABLE LIQUIDS.

Exposure Controls

Respiratory Protection:AVOID BREATHING VAPORS/SPRAY MIST, OPEN WINDOWS & DOORS MEANS TO ENSURE FRESH AIR ENTRY DURING DRYING. IF YOU EXPERIENCE EYE WATERING, HEADACHES, DIZZINESS. INCREASE FRESH AIR, WEAR RESPIRATORY PROTECTION (NIOSH/MSHA) TC23C OR EQUIVALENT).

Ventilation:PROVIDE SUFFICIENT MECHANICAL & LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:NEOPRENE

Eye Protection:GOGGLES, ARE ADVISED

Other Protective Equipment:THE EXPERT ASSISTANCE OF AN INDUSTRIAL HYGIENIST SHOULD BE SOUGHT.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM. MINIMIZE PERSONAL CONTACT & BREATHING OF VAPORS.

Supplemental Safety and Health

WT PER GAL: 7.0-8.0 (PAINT)

Chemical Properties

Boiling Pt:B.P. Text:133-331F

Melt/Freeze Pt:M.P/F.P Text: 1500F

Vapor Density:>AIR

Spec Gravity:Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT TO MODERATE

Appearance and Odor:TYPICAL SOLVENT PAINT

Percent Volatiles by Volume:85-90%

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, HEAT

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME

Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS, CO₂, CO, VARIOUS HYDROCARBONS, NITROGEN COMPOUNDS WHEN BURNED.

Disposal

Waste Disposal Methods:MATERIAL COLLECTED ON ABSORBENT MATERIAL MAY BE DEPOSITED IN A POSTED TOXIC SUBSTANCE LANDFILL IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.