

## **WET/DRY ROOF PATCH 3306**

### **MSDS Number**

BHBMV

### **National Stock Number**

8030-00F008624

### **Product Name**

WET/DRY ROOF PATCH 3306

### **Manufacturer**

GULF STATES ASPHALT CO INC

### **Product Identification**

Product ID:WET/DRY ROOF PATCH 3306

MSDS Date:08/31/1988

FSC:8030

NIIN:00F008624

MSDS Number: BHBMV

### **Responsible Party**

GULF STATES ASPHALT CO, INC.

300 CHRISTY PLACE

SOUTH HOUSTON , TX 77587

Emergency Phone: (713) 941-4410

Info Phone: (713) 941-4410

Cage: 22148

### **Contractor**

GULF STATES ASPHALT CO INC

HOUSTON, TX 77002-7905

US

Cage: 22148

### **Ingredients**

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100)

CAS: 64742-88-7

Fraction By Weight: 20-50%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

ASPHALT (PETROLEUM)

CAS: 8052-42-4

RTECS: CI9900000

Fraction By Weight: 50-80%

ACGIH TLV: 5 MG/M3; (FUME);9192

### **Hazards**

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: DIZZINESS, NAUSEA. SKIN:  
IRRITATION FROM DE-OILING. EYE: IRRITATION. OVEREXPOSURE TO

SOLVENTS ARE ASSOCIATED W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.  
INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE  
CONTENTS MAY BE HARMFUL OR FATAL.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: DIZZINESS, NAUSEA. SKIN: IRRITATION  
FROM DE-OILING. EYE: IRRITATION. OVEREXPOSURE TO SOLVENTS ARE  
ASSOCIATED WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.  
INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE  
CONTENTS MAY BE HARMFUL OR FATAL.

Medical Condition Aggravated by Exposure:BREATHING VAPORS OVER A LONG PERIOD  
OF TIME CAN IRRITATE BRONCHIAL MEMBRANES WITH POSSIBLE CHEMICAL  
PNEUMONIA.

## First Aid

First Aid:SKIN: REMOVE WITH MINERAL SPIRITS; WASH WITH SOAP & WATER.  
INHALATION: REMOVE TO FRESH AIR; IF EXCESSIVELY DIZZY, ADMINISTER  
OXYGEN. EYES: WASH WITH LARGE QUANTITIES OF WATER. IF IRRITATION  
PERSISTS, SEE A PHYSICIAN.

## Fire Fighting

Flash Point:>100F

Lower Limits:1%

Upper Limits:7%

Extinguishing Media:DRY CHEMICAL, ALCOHOL FOAM, WATER FOG, FOAM, CO2

Fire Fighting Procedures:TREAT AS ANY HYDROCARBON FIRE

Unusual Fire/Explosion Hazard:DON'T USE LIQUID WATER. THIS MAY CAUSE  
THE FIRE TO SPREAD.

## Accidental Release

Spill Release Procedures:SCOOP UP AND PLACE IN COVERED METAL CONTAINER.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM SPARKS, OPEN FLAMES, OR  
OTHER SOURCES OF IGNITION.

## Exposure Controls

Respiratory Protection:IF AREA CAN'T BE ADEQUATELY VENTILATED, USE  
SELF-CONTAINED BREATHING EQUIPMENT.

Ventilation:USE FORCED AIR VENTILATION TO MAINTAIN VAPOR Protective Gloves:NOT NORMALLY REQUIRED

Eye Protection:WEAR GLASSES, GOGGLES IF NECESSARY

Work Hygienic Practices:WASH HANDS WELL BEFORE EATING. CHANGE CLOTHES  
AT LEAST DAILY.

Supplemental Safety and Health

WT/GAL: 7.8-8.5 LBS. THE TLV FOR ASPHALT APPLIES TO ITS VAPOR STATE,  
I.E., WHEN HEATED. IT IS NOT APPLICABLE IN THIS PRODUCT.

## Chemical Properties

Boiling Pt:B.P. Text:>300-900F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:20-40%

## Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS SUCH AS NITRIC ACID.

Stability Condition to Avoid:KEEP AWAY FROM SOURCES OF FIRE.

## Disposal

Waste Disposal Methods:DISPOSE AS WITH ANY HYDROCARBON LIQUID.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their

particular situation.