

## **DESERT BEIGE**

### **MSDS Number**

BHBRK

### **National Stock Number**

8010-00F009210

### **Product Name**

DESERT BEIGE

### **Manufacturer**

GENERAL PAINT AND CHEMICAL

### **Product Identification**

Product ID:DESERT BEIGE

MSDS Date:01/24/1985

FSC:8010

NIIN:00F009210

MSDS Number: BHBRK

### **Responsible Party**

GENERAL PAINT & CHEMICAL

201 JANDUS ROAD

CARY , IL 60013

Emergency Phone: (312) 639-5383

Info Phone: (312) 639-5383

Cage: GENE A

### **Contractor**

GENERAL PAINT & CHEMICAL

CARY, IL 60013

(312) 639-5383

Cage: GENE A

### **Ingredients**

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100)

CAS: 64742-88-7

Fraction By Weight: 35-45%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: HEADACHE, DIZZINESS, NAUSEA. EYE: SEVERE IRRITATION. SKIN: DRYING.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: SEVERE IRRITATION. SKIN: DRYING.

INHALATION: HEADACHE, DIZZINESS & NAUSEA.

### **First Aid**

First Aid:EYES: WASH W/FRESH WATER. SKIN: WASH W/WATER & SOAP.

INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NECESSARY. GET MED ATT. INGESTION: DON'T INDUCE VOMITING. KEEP PERSON WARM & QUIET . GET MED ATT.

---

## Fire Fighting

Flash Point:105F  
Lower Limits:0.9%  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG  
Fire Fighting Procedures:TREAT AS VOLATILE LIQUID FIRE. WATER SPRAY MAY BE INEFFECTIVE. IF WATER SPRAY IS USED, FOG NOZZLES ARE PREFERABLE.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. ISOLATE FROM HEAT, SPARKS & OPEN FLAME.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. CONTAIN SPILL, ABSORB LIQUID W/CLAY, SAND/FLOOR ABSORBENT. PREVENT RUN-OFF TO SEWERS, STREAMS/OTHER BODIES OF WATER.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, & OPEN FLAMES. DON'T TAKE INTERNALLY. AVOID PROLONGED CONTACT W/SKIN. CONTAINERS SHOULD BE GROUNDED WHEN POURING.  
Other Precautions:AVOID FREE FALL OF MORE THAN 2-3 INCHES WHEN POURING.

## Exposure Controls

Respiratory Protection:NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IF TLV ARE EXCEEDED. APPROVED MECHANICAL FILTER TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATION.  
Ventilation:PROVIDE SUFFICIENT MECHANICAL/LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:REQUIRED  
Eye Protection:RECOMMENDED  
Other Protective Equipment:IMPERVIOUS CLOTHING & BOOTS.  
Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING/USING BATHROOM. DON'T REUSE CONTAMINATED CLOTHING.  
Supplemental Safety and Health  
WT PER GAL: VARIES W/COLOR.

## Chemical Properties

Boiling Pt:B.P. Text:300-380F  
Vapor Pres:2MM  
Vapor Density:>AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER

## Stability

Stability Indicator/Materials to Avoid:YES  
CONTACT W/STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:ISOLATE FROM HEAT, OPEN FIRE & SPARKS  
Hazardous Decomposition Products:CO, ACROLEIN & OXIDES OF NITROGEN

## Disposal

Waste Disposal Methods:CONTAMINATED ABSORBENT MAY BE DEPOSITED IN LANDFILL IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.