

SLATE GRAY

MSDS Number

BHBRL

National Stock Number

8010-00F009211

Product Name

SLATE GRAY

Manufacturer

GENERAL PAINT AND CHEMICAL

Product Identification

Product ID: SLATE GRAY
MSDS Date: 01/24/1985
FSC: 8010
NIIN: 00F009211
MSDS Number: BHBRL

Responsible Party

GENERAL PAINT & CHEMICAL
201 JANDUS ROAD
CARY, IL 60013
Emergency Phone: (312) 639-5383
Info Phone: (312) 639-5383
Cage: GENE A

Contractor

GENERAL PAINT & CHEMICAL
CARY, IL 60013
(312) 639-5383
Cage: GENE A

Ingredients

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100)
CAS: 64742-88-7
Fraction By Weight: 35-45%
OSHA PEL500 PPM
ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: INHALATION: HEADACHE, DIZZINESS,
NAUSEA. EYE: SEVERE IRRITATION. SKIN: DRYING.
Explanation of Carcinogenicity: NONE
Effects of Overexposure: EYES: SEVERE IRRITATION. SKIN: DRYING.
INHALATION: HEADACHE, DIZZINESS & NAUSEA.

First Aid

First Aid: EYES: WASH W/FRESH WATER. SKIN: WASH W/WATER & SOAP.
INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF
NECESSARY. GET MED ATT. INGESTION: DON'T INDUCE VOMITING. KEEP
PERSON WARM & QUIET . GET MED ATT.

Fire Fighting

Flash Point:105F
Lower Limits:0.9%
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG
Fire Fighting Procedures:TREAT AS VOLATILE LIQUID FIRE. WATER SPRAY MAY BE INEFFECTIVE. IF WATER SPRAY IS USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. ISOLATE FROM HEAT, SPARKS & OPEN FLAME.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. CONTAIN SPILL, ABSORB LIQUID W/CLAY, SAND/FLOOR ABSORBENT. PREVENT RUN-OFF TO SEWERS, STREAMS/OTHER BODIES OF WATER.

Handling

Handling and Storage Precautions:KEEP AWAY FROMM HEAT, SPARKS, & OPEN FLAMES. DON'T TAKE INTERNALLY. AVOID PROLONGED CONTACT W/SKIN. CONTAINERS SHOULD BE GROUNDED WHEN POURING.
Other Precautions:AVOID FREE FALL OF MORE THAN 2-3 INCHES WHEN POURING.

Exposure Controls

Respiratory Protection:NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IF TLV ARE EXCEEDED. APPROVED MECHANICAL FILTER TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATION.
Ventilation:PROVIDE SUFFICIENT MECHANICAL/LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:REQUIRED
Eye Protection:RECOMMENDED
Other Protective Equipment:IMPERVIOUS CLOTHING & BOOTS.
Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING/USING BATHROOM. DON'T REUSE CONTAMINATED CLOTHING.
Supplemental Safety and Health
WT PER GAL: VARIES W/COLOR.

Chemical Properties

Boiling Pt:B.P. Text:300-380F
Vapor Pres:2MM
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER

Stability

Stability Indicator/Materials to Avoid:YES
CONTACT W/STRONG OXIDIZING AGENTS
Stability Condition to Avoid:ISOLATE FROM HEAT, OPEN FIRE & SPARKS
Hazardous Decomposition Products:CO, ACROLEIN & OXIDES OF NITROGEN

Disposal

Waste Disposal Methods:CONTAMINATED ABSORBENT MAY BE DEPOSITED IN LANDFILL IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.