

1653 DEEP BASE

MSDS Number

BHBRT

National Stock Number

8010-00F009359

Product Name

1653 DEEP BASE

Manufacturer

DEVOE AND RAYNOLDS CO

Product Identification

Product ID:1653 DEEP BASE

MSDS Date:01/13/1987

FSC:8010

NIIN:00F009359

MSDS Number: BHBRT

Responsible Party

DEVOE & RAYNOLDS CO.

4000 DUPONT CIRCLE

LOUISVILLE , KY 40207

Emergency Phone: (502) 589-9340

Info Phone: (502) 589-9340

Cage: EO559

Contractor

DEVOE COATINGS CO DIV OF GROW GROUP INC

RIVERSIDE, CA 92507-2606

US

Cage: 70506

Ingredients

WATER, H2O

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 40-60%

ACRYLIC RESIN

Fraction By Weight: 25%

TEXANOL, 1,3-PENTANEDIOL 2,2,4-TRIMETHYL MONOISOBUTYRATE

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight:

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 3-20%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

SILICA, AMORPHOUS, DIATOMACEOUS EARTH, CONTAINING LESS THAN

CAS: 61790-53-2

RTECS: HL8600000

Fraction By Weight:

OSHA PEL20 MPPCF

ACGIH TLV: 10 MG/M3 TDUST; 9293

KAOLIN

CAS: 1332-58-7

RTECS: GF1670500

Fraction By Weight: 5-10%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 2 MG/M3 TDUST; 9293

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

3-iodo-2-propynyl butyl carbamate

CAS: 55406-53-6

RTECS: EZ0950000

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF THE RESPIRATORY TRACT, HEADACHE, NAUSEA, DIZZINESS. SKIN/EYE: PRIMARY IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: IRRITATION OF THE RESPIRATORY TRACT, HEADACHE, NAUSEA, DIZZINESS. SKIN/EYE: PRIMARY IRRITATION. PROLONGED/REPEATED BREATHING OF SPRAY MISTS/SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DU ST DISEASE OF THE LUNGS.

Medical Cond Aggravated by Exposure:NONE

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN FOR MED

TREATMENT. SKIN: REMOVE W/SOAP & WATER. REMOVE SOILED CLOTHING.
INGESTION: DRIN 1-2 GLASSES OF WATER TO DILUTE. DON'T INDUCE
VOMITING. CONSULT PHYSICIAN.

Fire Fighting

Flash Point:NONE
Lower Limits:0.62%
Upper Limits:3.2%
Extinguishing Media:CO2, DRY CHEMICAL, FOAM/NATIONAL FIRE PROTECTION
ASSOCIATION NFPA APPROVED METHOD FOR TREATING A CLASS B FIRE.
Fire Fighting Procedures:USE FULL PROTECTIVE EQUIPMENT INCLUDING SCBA.
WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE
PREFERABLE.
Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CLOSED
CONTAINERS/PREVENT PRESSURE BUILD-UP/POSSIBLE AUTO-IGNITION/HEAT.

Accidental Release

Spill Release Procedures:WASH W/WATER. CONTAIN SPILLED MATERIAL &
REMOVE W/INERT ABSORBENT. STORE IN CLOSED CONTAINER UNTIL PROPERLY
DISPOSED OF.

Handling

Handling and Storage Precautions:DON'T BREATHE VAPORS, SPRAY
MIST/SANDING DUST. DON'T GET IN EYES. STORE FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE.
Other Precautions:DON'T REUSE EMPTY CONTAINERS. KEEP OUT OF REACH OF
CHILDREN. USE NIOSH/MSHA APPROVED RESPIRATORS WHEN FLAME CUTTING,
WELDING, BRAZING & SANDING MATERIAL COATED WITH THIS PRODUCT.

Exposure Controls

Respiratory Protection:IN AREAS W/UNRESTRICTED VENTILATION & DURING
SANDING/GRINDING OPERATIONS, USE NIOSH/MSHA APPROVED MECHANICAL
FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY &
SANDING DUST. WEAR NIOS H/MSHA APPROVED AIR SUPPLY/HOODS.
Ventilation:PROVIDE ADEQUATE MECHANICAL/LOCAL EXHAUST VENTILATION TO
KEEP Protective Gloves:NOT REQUIRED
Eye Protection:SAFETY EYEWEAR W/SIDESHIELDS RECOMMENDED
Work Hygienic Practices:REMOVE/WASH SOILED CLOTHING BEFORE REUSE. WASH
HANDS BEFORE EATING, SMOKING/USING THE WASHROOM.
Supplemental Safety and Health
WT PER GAL: 9.32-10.82 LBS

Chemical Properties

Boiling Pt:B.P. Text:212-490F
Vapor Density:Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:69.7%

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:HEAT, FLAME
Hazardous Decomposition Products:CO, CO2, OXIDES OF NITROGEN & METALS.
MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &
FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DON'T
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.