

146 6416 EASTMAN COLOR DEVELOPING AGENT, CD-2 (50LBS)

MSDS Number

BHBTT

National Stock Number

6750-00-965-4606

Product Name

146 6416 EASTMAN COLOR DEVELOPING AGENT, CD-2 (50LBS)

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:146 6416 EASTMAN COLOR DEVELOPING AGENT, CD-2 (50LBS)

MSDS Date: 10/25/1995

FSC:6750

NIIN:00-965-4606 MSDS Number: BHBTT

Responsible Party

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER, NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 800- 242-2424

Cage: 19139

Contractor

EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

ROCHESTER, NY 14650-3129

800-828-6203

US

Cage: 5K871

Ingredients

4-N,N-DIETHYL-2-METHYLPHENYLENEDIAMINE MONOHYDROCHLORIDE

CAS: 2051-79-8 RTECS: SS9560000

Fraction By Weight: 100%

Hazards

LD50 LC50 Mixture:ORAL LD50 RAT:F 107MG/KG;M 132MG/KG.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: MAY CAUSE LIVER DAMAGE BASED ON ANIMAL

DATA. INHAL:HARMFUL.AIRBORNE DUST IRRIT. EYE:AIRBORNE DUST IRRIT.HOWEVER IMMED FLUSHING OF EYE W/WATER WILL MIN ANY IRRIT EFFECT. SKIN: MAY CAUSE ALLERGIC SKIN RE ACTION. INGEST: HARMFUL. Explanation of Carcinogenicity: PER MSDS: CARCINOGENICITY CLASSIFICATION

IARC/ACGIH/NTP/OSHA: NONE.

Effects of Overexposure:LIVER DAMAGE, HARMFUL IF INGEST/INHAL. EYE

IRRIT, ALLERGIC SKIN REACTION.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.



First Aid

First Aid:INHAL:MOVE TO FRESH AIR.NOT BREATH GIVE ART RESP.DIFFI BREATH GIVE OXY.GET MED ATTN IMMED. EYE:IMMED FLUSH W/PLENTY OF WATER FOR @LEAST 15MINS.GET MED ATTN. SKIN:IMMED FLUSH W/PLENTY OF WATER FOR @LEA ST 15MINS WHILE REMOVING CONTAMIN CLLTH/SHOES.GET MED ATTN. INGEST:INDUCE VOMIT AS DIRECTED BY MED PERSONNEL.CALL PHYSICIAN/POIS CNTRL CNTR IMMED.NEVER GIVE ANYTHING BY MOUTH TO UNCONSC PERSON.

Fire Fighting

Extinguishing Media: WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE (CO2). Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING.FIRE/EXCESSIVE HEAT MAY PRODUCE HAZ DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:POWDERED MATL MAY FORM EXPLOSIVE DUST-AIR MMXTURES. FIRE/HIGH TEMPS MAY CAUSE EXPLOSIVE DECOMPOSITION. COMBUSTIBLE SOLID.

Accidental Release

Spill Release Procedures: SWEEP OR SCOOP UP & REMOVE. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: AVOID CONTACT W/EYE/SKIN/CLOTH. AVOID BREATH DUST. USE W/ADEQUATE VENTI. KEEP FROM CONTACT W/OXIDIZING MATLS. KEEP CNTNR CLSD.

Other Precautions:REF:NFPA PAMPHLET654:"PREVENTION OF FIRE/DUST EXPLO IN CHEM/DYE/PHARM/PLAST INDUSTRIES".PROPERTIES:LOW BIOCHEM OXY DEMAND;LITTLE POT TO CAUSE OXY DEPLETION IN AQU SYS;HI POT TO AFFECT SOME AQUA ORGANI SMS & GERMINATION &/OR EARLY GROWTH(SUP)

Exposure Controls

Respiratory Protection:IF ENGINEERING CONTROLS DO NTO MAINTAIN AIRBORNE CONCEN BELOW RECOMMENDED EXPOSURE LIMITS AN APPROVED RESP MUST BE WORN.RESP TYP:DUST.IF RESP USED PROGRAM SHOULD BE INSTITUTED TO ASSURE COMPLIANCE W/O SHA STD 29CFR 1910.134.

Ventilation: USE GOOD GEN VENTI(TYP 10AIR CHANGES/HR). MATCH VENTI RATES W/CONDITIONS. USE PROCESS ENCLOSURES/LOC EXHAU/OTHER (SUPPLEM) Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment: BOOTS, PROTECTIVE CLOTHING APPROPRIATE FOR RISK EXPO. EYEBATH, SAFETY SHOWER, WASHING FACILITIES.

Work Hygienic Practices: WASH CONTAMIN CLOTH BEF

REUSE.DESTROY/THOROUHGLY CLEAN CONTAMIN SHOES.WASH THOROUGHLY AFT HNDLG.

Supplemental Safety and Health

PH:6.0(@10G/L WATER). OTHER PRECAUT:OF SOME PLANTS & GROWTH OF SOME PLATN SEEDLINGS;LOW POT TO PERSIST IN ENVIRO & TO BIOCONCEN.AFT DIL W/LG AMTS OF WATER @ 2ND WASTE TREAT MATL NOT EXPECTED TO CAUSE ADVERSE ENVIRO EFFECTS. VENTI:ENGINEERING CNTRLS TO MAINTAIN AIRBORNE LEVELS BEL RECOMMENDED EXPO LIMITS.

Chemical Properties

HCC:T4

Melt/Freeze Pt:M.P/F.P Text:500F,260C Decomp Temp:Decomp Text:500F,260C

Vapor Pres: NEGLIGIBLE

Vapor Density: 7.1

Spec Gravity: N/AVAILABLE

pH:SUPPLE

Solubility in Water: APPRECIABLE

Appearance and Odor: SOLID (CRYSTAL), WHITE COLOR, ODORLESS.

Percent Volatiles by Volume: N/APPL

Stability



Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:MINIMIZE DUST GENERATION & ACCUMULATION. MATL CAN DECOMPOSES ABOVE 255C(491F).AVOID TEMPS >155C(311F). Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, HYDROGEN CHLORIDE, OXIDES OF NITROGEN.

Disposal

Waste Disposal Methods:DISCHARGE/TREAT/DISPOSAL MAY BE DUBJ TO NAT/STATE/LOC LAWS.INCINERATE.SINCE EMPTIED CNTNRS RETAIN PROD RESIDUE FOLLOW LABEL WARN EVEN AFT CNTNR IS EMPTIED.CHEM SUBJ TO REPORT REQMTS OF SEC 313 TITLE I II SARA/40CFR PART 372:NONE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.