

LACQUER C/N GLOSS 21 BLUE 15044 ID786504

MSDS Number

BHBWP

National Stock Number

8010-00-242-6318

Product Name

LACQUER C/N GLOSS 21 BLUE 15044 ID786504

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:LACQUER C/N GLOSS 21 BLUE 15044 ID786504

MSDS Date:12/15/1988

FSC:8010

NIIN:00-242-6318

MSDS Number: BHBWP

Responsible Party

PRATT & LAMBERT INC.

16116 E 13TH ST

WICHITA , KS 67201

US

Preparer: W.A. ELLISON

Cage: PRATT

Contractor

PRATT AND LAMBERT INC

2153

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

NITROCELLULOSE

CAS: 9004-70-0

RTECS: QW0970000

OSHA PELNONE ESTABLISHED

ACGIH TLV: NONE ESTABLISHED

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS: 8002-05-9

RTECS: SE7449000

OSHA PEL400 PPM

ACGIH TLV: 400 PPM; 8990

DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA

CAS: 117-81-7

RTECS: TI0350000

OSHA PEL5 MG/M3/10 STEL

ACGIH TLV: 5 MG/M3; 9192

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: DE3030000

OSHA PEL100 PPM

VOL ORGANIC CMPD 5.3 LB/GL LESS WATER & NPRS* 600 G/L LESS

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:SWALLOWING/GASTROINTESTINAL IRRITATION,NAUSEA,VOMITING. INHALATION/MAY CAUSE NOSE,THROAT IRRIT. HIGH CONCENTRATIONS MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION. EYE/IRRITATION. SKIN/MAY CAUSE DE FATTING, IRRITATION OF THE SKIN.

Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS A POTENTIAL CARCINOGEN BY THE NATURAL TOXICOLOGY PROGRAM.

Effects of Overexposure:PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM

DAMAGE. DELIBERATE CONCENTRATION AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

First Aid

First Aid:SWALLOWING/DO NOT INDUCE VOMITING. GET MED ATTN. INHALATION/GET FRESH AIR IMMED.IF BREATHING HAS STOPPED,GIVE ARTIFICIAL RESPIRATION.GET MED ATTN. EYE/FLUSH WITH LG AMT OF WATER FOR 15 MIN. GET MED AT TN. SKIN/FLUSH THE CONTAMINATED AREA W/LG AMT OF WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A DR. NOTE TO DR. ANY TREATMENT FOR OVEREXP S/B DIRECTED AT THE CONTROL OF SYMPTOMS & CLINICAL CONDITIONS.

Fire Fighting

Flash Point:20F/-6.67C
Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL EXPOSED CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PROD MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMED APPARENT. OBTAIN MEDICAL ATTN. WARNING:FLAMMABLE.

Accidental Release

Spill Release Procedures:ELIM ALL IGNITION SOURCES. DIKE & CONTAIN SPILL WITH INERT MATERIAL. USE COVERED METAL CONT FOR RECOVERY OR DISPOSAL. USE ONLY NON-SPARKING TOOLS. DONT CONTAMINATE SEWERS,STREAMS AND GROUNDWATER. KEEP SPECTATORS AWAY. WEAR APPROPRIATE RESPIRATORS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:DO NOT REUSE CONTAINERS. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD/BRAZE/CUT ON EMPTY CONT. NEVER USE PRESSURE TO EMPTY.DRUM NOT A PRESSURE VESSEL. CLOSE AFTER EACH USE. DO NOT TAKE INTERNALLY.

Exposure Controls

Respiratory Protection:IN RESTRICTED AREAS A NIOSH RESPIRATOR MAY BE REQUIRED. CONFINED AREAS A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR. SEE OSHA 29CFR1910.134. RESPIRATORY PROTECTION AND RESPIRATORY PROTECTION MANUAL AND GUIDELINE, AMER IND HYGIENE ASSOC.
Ventilation:GENERAL AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME AND PATTERN TO MAINTAIN CONCENTRATIONS OF SUBSTANCES.
Protective Gloves:IMPERMEABLE GLOVES.
Eye Protection:SAFETY SPECTACLES.
Other Protective Equipment:NOT LIKELY TO BE NEEDED.
Supplemental Safety and Health
NONE LISTED.

Chemical Properties

Boiling Pt:B.P. Text:180F/302F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:78

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.
Hazardous Decomposition Products:BURNING/WELDING/CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE. OXIDES OF NITROGEN MAY BE GENERATED.
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT,SPARKS AND

FLAME.

Disposal

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY.DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. DISPOSE IAW FEDERAL,STATE AND LOCAL LAWS/REGULATIONS. RCRA CLASS IFICATION D001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.