
LACQUER C/N GLOSS 01 WHITE 17875 ID786716

MSDS Number

BHBXC

National Stock Number

8010-00-257-5377

Product Name

LACQUER C/N GLOSS 01 WHITE 17875 ID786716

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:LACQUER C/N GLOSS 01 WHITE 17875 ID786716

MSDS Date:12/15/1988

FSC:8010

NIIN:00-257-5377

MSDS Number: BHBXC

Responsible Party

PRATT AND LAMBERT INC

16116 E 13TH ST

WICHITA , KS 67201

US

Emergency Phone: 716-873-6000 DOT EMER 8002553924

Info Phone: 316-733-1361

Preparer: W.A. ELLISON

Cage: 61196

Contractor

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM/500 STEL
ACGIH TLV: 400 PPM/500STEL;9192

NITROCELLULOSE
CAS: 9004-70-0
RTECS: QW0970000
OSHA PELNONE ESTABLISHED
ACGIH TLV: NONE ESTABLISHED

ISOPROPYL ALCOHOL (SARA III)
CAS: 67-63-0
RTECS: NT8050000
OSHA PEL400 PPM/500 STEL
ACGIH TLV: 400 PPM/500STEL;9192

TITANIUM DIOXIDE
CAS: 13463-67-7
RTECS: XR2275000
OSHA PEL15 MG/M3 TDUST
ACGIH TLV: 10 MG/M3 TDUST; 9293

NAPHTA (PETROLEUM SPIRITS OR BENZIN)
CAS: 8030-30-6
RTECS: DE3030000
OSHA PEL100 PPM

DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA
CAS: 117-81-7
RTECS: TI0350000
OSHA PEL5 MG/M3/10 STEL
ACGIH TLV: 5 MG/M3; 9192
EPA Report Quantity: 100 LBS
DOT Report Quantity: 100 LBS

N-HEPTANE
CAS: 142-82-5
RTECS: MI7700000
OSHA PEL500 PPM/500 STEL
ACGIH TLV: 400 PPM/500STEL;9293

VOL ORGANIC CMPD 5.0 LB/GL LESS WATER & NPRS* 600 G/L LESS

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:NO
Health Hazards Acute and Chronic:SWALLOWING CAN CAUSE GASTROINTESTINAL IRRITATION,NAUSEA AND VOMITING. INHALATION MAY CAUSE NOSE OR THROAT IRRITATION. EYE-MAY CAUSE EYE IRRITATION. SKIN PRIMARY SKIN IRRITANT. MAY CAUSE DEFATTING AND IRRITATION OF THE SKIN. HIGH CONCENTRATIONS MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION.
Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS A POTENTIAL CARCINOGEN BY THE NATIONAL TOXICOLOGY PROGRAM.
Effects of Overexposure:REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE C ONTENTS MAY BE HARMFUL OR FATAL.

First Aid

First Aid:SWALLOWING:DO NOT INDUCE VOMITING. GET MED ATTN;
INHALATION:REMOVE TO FRESH AIR IMMED AND GET MED ATTN. EYE:FLUSH WITH LARGE AMOUNTS OF WATER AT LEAST 15 MIN. GET MED ATTN.
SKIN:FLUSH THE CONTAMINATED AREA WITH WATER. REMOVE CLOTHING.CONSULT A PHYSICIAN. NOTE TO PHYSICIAN ANY TREATMENT THAT MIGHT BE REQUIRED FOR OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS

Fire Fighting

Flash Point:20F/-6.67C
Extinguishing Media:CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WTR MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS. IF WTR USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:DURING EMERGENCY COND OVEREXP TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT.OBTAIN MEDICAL ATTN;WARNING:FLAMMABLE

Accidental Release

Spill Release Procedures:ELIMINATE IGNITION SOURCES. USE ONLY NON-SPARKING TOOLS.DIKE WITH INERT MATERIAL.PUT IN METAL CONTAINERS FOR DISPOSAL. PREVENT CONTAMINATION OF SEWERS,STREAMS, AND GROUNDWATER.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.DO NOT REUSE CONTAINERS.DO NOT WELD/BRAZE/CUT ON CONTAINERS.NEVER USE PRESSURE TO EMPTY. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER.

Exposure Controls

Respiratory Protection:RESTRICTED VENTILATION A NIOSH CHEMICAL RESPIRATOR MAY BE REQUIRED. IN CONFINED AREAS USE NIOSH/MSHA APPROVED AIR RESPIRATOR. REFER TO OSHA 29CFR1910.134 AND RESPIRATORY PROTECTION A MANUAL AND GUIDELINE, AMERICAN HYGIENE ASSOC.
Ventilation:PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME AND PATTERN TO MAINTAIN CONCENTRATIONS.
Protective Gloves:SOLVENT IMPERMEABLE GLOVES.
Eye Protection:WEAR SAFETY SPECTACLES.
Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.
Supplemental Safety and Health
NONE LISTED.

Chemical Properties

HCC:F2

Boiling Pt:B.P. Text:181F/302F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:75

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF
IGNITION.
Hazardous Decomposition Products:BURNING/WELDING/CUTTING WILL PRODUCE
SMOKE,CARBON MONOXIDE & CARBON DIOXIDE. IN ADDITION OXIDES OF
NITROGEN MAY BE GEN.
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT,SPARKS AND
FLAME.

Disposal

Waste Disposal Methods:DISPOSE IAW FEDERAL,STATE AND LOCAL
LAWS.INCINERATE IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED
CONTAINERS. MATERIAL TO BE DISPOSED OF IN A HAZARDOUS WASTE
LANDFILL.RCRA CLASSIFICATION D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.