

LUBRICATING OIL 60,505-15W40

MSDS Number

BHBXS

National Stock Number

9150-01-152-4118

Product Name

LUBRICATING OIL 60,505-15W40

Manufacturer

BATTENFIELD AMERICA INC

Product Identification

Product ID:LUBRICATING OIL 60,505-15W40

MSDS Date:04/17/1989

FSC:9150

NIIN:01-152-4118

MSDS Number: BHBXS

Responsible Party

BATTENFIELD AMERICA,INC.

1575 CLINTON ST.

BUFFALO , NY 14206

Emergency Phone: 716-822-8410

Info Phone: 716-822-8410

Preparer: THOMAS G. MUSILLI

Cage: KO105

Contractor

BATTENFIELD AMERICA,INC.

BUFFALO, NY 14206

US

716-822-8410

Cage: KO105

Ingredients

MINERAL OIL

CAS: 64742-65-0

RTECS: PY8038500

Fraction By Weight: 79.2%

OSHA PEL5 MG/M3 OIL MIST

ACGIH TLV: 5 MG/M3 OIL MIST

LUBRIZOL 4837 (LUBRIZOL, CLEVELAND OH)

ACRYLIC COPOLYMER (ROHM & HAAS, PHILADELPHIA,PA)

Fraction By Weight: 0.20%

STYRENE-ISOPRENE COPOLYMER

Fraction By Weight: 11.60%

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MFR STATES "THIS PRODUCT HAS BEEN USED FOR YEARS WITH NO KNOWN ILL EFFECTS". THE MOST LIKELY HEALTH HAZARD IS INHALATION OF OIL MIST IN THE UNLIKELY EVENT THAT THE PRODUCT BECOMES AN AIRBORNE MIST.
Effects of Overexposure:PRODUCT MAY IRRITATE EYES,SKIN. UNDER NORMAL USE,SHOULD NOT BE INHALED OR INGESTED.
Medical Cond Aggravated by Exposure:NONE

First Aid

First Aid:EYE:FLUSH WITH WATER FOR 15 MIN. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP & WATER. LAUNDER CLOTHING BEFORE REUSE. INHALED:(HIGHLY UNLIKELY)REMOVE FROM EXPOSURE. GET MEDICAL CARE. INGESTED:DO NOT INDUCE VOMITING. GET MEDICAL CARE.

Fire Fighting

Flash Point Method:COC
Flash Point:440F/227C
Autoignition Temp:Autoignition Temp Text:470F
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM,SAND/EARTH,WATER FOG.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY CAUSE FROTHING.
Unusual Fire/Explosion Hazard:NONE.

Accidental Release

Spill Release Procedures:RECOVER LIQUID IF POSSIBLE.ADSORB REMAINDER WITH INERT MATERIAL.
Neutralizing Agent:NONE

Handling

Handling and Storage Precautions:STORE AWAY FROM HEAT,SPARKS,OPEN FLAMES.

Exposure Controls

Respiratory Protection:NONE IS EXPECTED TO BE NECESSARY. WEAR NIOSH/MSHA APPROVED RESPIRATOR IF EXPOSED ABOVE PEL/TLV OF OIL MIST.
Ventilation:NORMAL ROOM VENTILATION.
Protective Gloves:NEOPRENE OR BUTYL.
Eye Protection:SAFETY GLASSES,SPLASH GOGGLES.
Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE.
Supplemental Safety and Health

Chemical Properties

HCC:V6
Boiling Pt:B.P. Text:700F/371C
Spec Gravity:0.89
Solubility in Water:NIL
Appearance and Odor:FLUID,OIL,BLAND ODOR.
Percent Volatiles by Volume:0

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS.
Stability Condition to Avoid:HEAT,IGNITION SOURCES SUCH AS SPARKS & OPEN FLAME.
Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE.

Disposal

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.

MFR SUGGESTS RECYCLE (PREFERRABLE) OR INCINERATE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.