

SOFT-GLO SEMI-GLOSS (FED. SPEC NO. TT-E-529

MSDS Number

BHCDP

National Stock Number

8010-00N008659

Product Name

SOFT-GLO SEMI-GLOSS (FED. SPEC NO. TT-E-529

Manufacturer

UNIVERSAL PAINT CORPERATION

Product Identification

Product ID:SOFT-GLO SEMI-GLOSS (FED. SPEC NO. TT-E-529 MSDS Date:05/29/1986 FSC:8010 NIIN:00N008659 MSDS Number: BHCDP

Responsible Party

UNIVERSAL PAINT CORPERATION

111 HUDSON AVE.

INDUSTRY, CA 91744

Emergency Phone: 818-916-6271

Info Phone: 818-961-6271

Cage: 34691

Contractor

UNIVERSAL PAINT COPR

INDUSTRY, CA 91744

US

818-961-6271

Cage: 34691

Ingredients

1.0%.

CAS: 64742-88-7

Fraction By Weight: 32%

OSHA PELN/K

ACGIH TLV: 100 PPM (MFR)

Hazards

LD50 LC50 Mixture:N/K Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:DERMATITIS Explanation of Carcinogenicity:NONE Effects of Overexposure:EYES:IRRIT,REDNESS,TEARING,BLURRED VISION.SKIN:IRRIT,DERMATITIS.INGESTION:GI IRRIT,NAUSEA,VOMITING,AND DIARRHEA,ASPIRATION INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONNITIS,WHICH CAN BE FATAL.INHALATION: NASAL,NAUSEA,HEADACHE,POSSIBLE UNCONSCIOUSNESS,AND EVEN ASPHYXIATION. Medical Cond Aggravated by Exposure:N/K

First Aid



First Aid:EYES:FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MIN LIFTING UPPER & LOWER LIDS OCCASIONALLY.GET MED ATTENTION.SKIN:WASH WITH SOAP & WATER.REMOVE CONTAMINATED CLOTHING.INGESTION:DO NOT INDUCE VO MITING.KEEP PERSON WARM,QUIET,AND GET MEDICAL ATTENTION,INHALATION:IF AFFECTED REMOVE TO FRESH AIR.IF BREATHING HAS STOPPED.GIVE ARTIFICIAL RESPIRATION AND GET IMMEDIATE MEDICAL ATTENTION.

•

Fire Fighting

Flash Point:104F,40C

Lower Limits:1.0%

Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL. Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .DO NOT USE WATER.EXCLUDE AIR. Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION & IGNITED BY HEAT,HAZ DECOMP PRODUCTS:CO*2,VARIOUS HYDROCARBONS,ETC.

Accidental Release

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION.DIKE AREA AROUND SPILL.ABSORB LIQUID ON PAPER FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL. Neutralizing Agent: N/K

Handling

Handling and Storage Precautions:STORE AWAY FROM HEAT AND OPEN FLAME. Other Precautions:CONTAINERS WHEN EMPITIED MAY BE HAZARDOUS DUE TO PRODUCT RESIDUES.ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . Ventilation:LOCAL AND GENERAL VENTILATION NECESSARY TO KEEP AIR CONCENTRATION BELOW TLV . Protective Gloves:WEAR RESISTANT GLOVES,SUCH AS BUNA-N. Eye Protection:CHEMICAL WORKERS GOGGLES . Other Protective Equipment:IMPERVIOUS CLOTHING AND BOOTS. Work Hygienic Practices:N/K Supplemental Safety and Health NONE

Chemical Properties

Boiling Pt:B.P. Text:280-400F Melt/Freeze Pt:M.P/F.P Text:N/K Decomp Temp:Decomp Text:N/K Vapor Pres:N/K Vapor Density:>AIR Spec Gravity:1.2 (WATER=1) Evaporation Rate & Reference:SLOWER THAN ETHER. Solubility in Water:N/K Appearance and Odor:N/K Percent Volatiles by Volume:50

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:OPEN FLAME. Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE,VARIOUS HYDROCARBONS,ETC. Conditions to Avoid Polymerization:OPEN FLAME.

Disposal

Waste Disposal Methods: DISPOSAL MUST IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS .



https://msdsreport.com/msds/BHCDP

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.