

LAC SPRAYING II WHITE 17875 ID 793716

MSDS Number

BHCFM

National Stock Number

8010-00-165-6140

Product Name

LAC SPRAYING II WHITE 17875 ID 793716

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:LAC SPRAYING II WHITE 17875 ID 793716

MSDS Date:12/15/1988

FSC:8010

NIIN:00-165-6140

MSDS Number: BHCFM

Responsible Party

PRATT & LAMBERT, INC.

16116 E 13TH ST

WICHITA , KS 67201

US

Preparer: W.A. ELLISON

Cage: FO127

Contractor

PRATT AND LAMBERT INC

22

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

NITROCELLULOSE

CAS: 9004-70-0

RTECS: QW0970000

OSHA PELNONE ESTABLISHED

ACGIH TLV: NONE ESTABLISHED

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: DE3030000

OSHA PEL100 PPM

DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA

CAS: 117-81-7

RTECS: TI0350000

OSHA PEL5 MG/M3/10 STEL

ACGIH TLV: 5 MG/M3; 9192

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

ALIPHATIC HYDROCARBON (VP MM HG @ 20 DEG C 12)

CAS: 64742-89-8

OSHA PELNONE ESTABLISHED

ACGIH TLV: NONE ESTABLISHED

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

VOL ORGANIC CMPD 5.5 LB/GL LESS WATER & NPRS* 660 G/L LESS

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SWALLOWING-GASTROINTESTINAL
IRRITATION, NAUSEA, VOMITTING. INHALATION-NOSE/THROAT
IRRITATION/HEADACHES,DIZZINESS/NAUSEA AND CONFUSION.
EYE-IRRITATION. SKIN PRIMARY IRRITANT, MAY CAUSE DEFATTING/IRRITA
TION OF THE SKIN.
Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS A
POTENTIAL CARCINOGEN AS LISTED BY THE NATIONAL TOXICOLOGY PROGRAM.
Effects of Overexposure:OVEREXPOSURE TO TOLUENE MAY CAUSE LIVER DAMAGE.
OVEREXPOSURE TO SOLVENTS-PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE.
INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.
Medical Cond Aggravated by Exposure:SWALLOWING-DO NOT INDUCE
VOMITING/GET MED ATTN. INHALATION-REMOVE TO FRESH AIR/GIVE
ARTIFICIAL RESPIRATION IF REQ/GET MED ATTN. EYE-FLUSH WITH
WATER/GET MED ATTN. SKIN-WASH WITH WATER.CONSULT A DOCTOR

First Aid

First Aid:NOTES TO PHYSICIAN-ANY TREATMENT THAT MIGHT BE REQUIRED FOR
OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE
CLINICAL CONDITIONS.

Fire Fighting

Flash Point:20F/-6.67C
Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM
IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:FOG NOZZLES ARE PREFERABLE IF WATER IS USED.
WEAR SELF CONTAINED BREATHING APPARATUS. USE WATER TO COOL
CONTAINERS.
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION MAY CAUSE
HEALTH HAZARD. GET MEDICAL ATTN.

Accidental Release

Spill Release Procedures:WEAR APPROPRIATE RESPIRATORS/ELIMINATE ALL
IGNITION SOURCES/DIKE SPILL WITH INERT MATERIAL/RECOVER & DISPOSE
OF IN METAL CONTAINERS. DO NOT CONTAMINATE
SEWERS/STREAMS/GROUNDWATER.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QTY IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:DO NOT WELD/BRAZE/CUT ON EMPTY CONTAINER-NEVER USE PRESSURE TO EMPTY-DRUM IS NOT A PRESSURE VESSEL.
CONTAINERS-GROUNDED/BONDED TO THE RECEIVING CONTAINER.DO NOT RE-USE CONTAINERS. CLOSE AFTER EACH USE . DO NOT TAKE INTERNALLY.

Exposure Controls

Respiratory Protection:IN RESTRICTED VENTILATION A NIOSH APPROVED RESPIRATOR. IN CONFINED AREAS USE A NIOSH/MSHA APPROVED RESPIRATOR. REFER TO OSHA 29CFR1910.134 AND RESPIRATORY PROTECTION A MANUALE AND GUIDELINE AMERICAN I NDUSTRIAL HYGIENE ASSOC.
Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION TO MAINTAIN HAZARDOUS SUBSTANCES LISTED IN SEC II BELOW THE LOWEST LIMITS.
Protective Gloves:SOLVENT IMPERMEABLE GLOVES.
Eye Protection:WEAR SAFETY SPECTACLES.
Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWERS.
Supplemental Safety and Health
NONE

Chemical Properties

Boiling Pt:B.P. Text:175F/302F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:81

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.
Hazardous Decomposition Products:BURNING/WELDING/CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE & CARBON DIOXIDE PLUS OXIDES ON NITROGEN MAY BE GENERATED.
Conditions to Avoid Polymerization:WILL NOT OCCUR.KEEP AWAY FROM HEAT,SPARKS AND FLAME.

Disposal

Waste Disposal Methods:DISPOSE IAW FEDERAL/STATE/LOCAL LAWS.INCINERATE ONLY IN EPA PERMITTED FACILITY. CONTAMINATED ABSORBANT DISPOSE OF IN A HAZARDOUS WASTE LANDFILL IAW FEDERAL/STATE/LOCAL REGULATIONS. RCRA CLASSIFICATION D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.