

## **DECONTAMINATING AGENT DS2**

### **MSDS Number**

BHCHJ

### **National Stock Number**

4230-01-133-4124

### **Product Name**

DECONTAMINATING AGENT DS2

### **Manufacturer**

U S ARMY ARMAMENT MUNITIONS AND CHEMICAL COMMAND

### **Product Identification**

Product ID:DECONTAMINATING AGENT DS2

MSDS Date:09/28/1984

FSC:4230

NIIN:01-133-4124

MSDS Number: BHCHJ

### **Responsible Party**

U.S. ARMY ARMAMENT,MUNITIONS & CHEMICAL COMMAND

SMCCR-SFS, HDQ. BLDG. E5101

ABERDEEN PROVING GROUND , MD 21010-5423

US

Emergency Phone: 301-671-4411 (0800 - 1630 EST)

Info Phone: 301-278-5201 (AFTER DUTY HOURS)

Cage: 80700

### **Contractor**

U.S. ARMY ARMAMENT,MUNITIONS & CHEMICAL COMMAND

ABERDEEN PROVING GROUND, MD 21010-5423

US

301-278-5201 (AFTER DUTY HOURS)

Cage: 80700

### **Ingredients**

DIETHYLENE TRIAMINE

CAS: 111-40-0

RTECS: IE1225000

Fraction By Weight: 69.-71%.

OSHA PEL1 PPM

ACGIH TLV: S, 1 PPM; 9192

2-METHOXYETHANOL (EGME) (SARA III)

CAS: 109-86-4

RTECS: KL5775000

Fraction By Weight: 27.-29%.

OSHA PELS, 25 PPM

ACGIH TLV: S, 5 PPM; 9192

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: CORROSIVE TO TISSUE & HIGHLY IRRITANT TO RESPIRATORY TRACT; CHRONIC: REPEATED EXPOSURE TO "DETA" CAN CAUSE SKIN SENSITIZATION & ASTHMA; SUFFICIENT EXPOSURE TO "EGME" MAY CAUSE "CNS" DEPRESSION & LIVER DAMAGE. ALTHOUGH NOT DEFINITELY ESTABLISHED IN HUMANS, REPRODUCTIVE EFFECTS ARE ALSO A MAJOR CONCERN.  
Effects of Overexposure:NO TOX. DATA AVAILABLE ON DS2. HOWEVER, DS2: ALKALI WHICH ON CONTACT WILL CORRODE TISSUE. EFFECTS EXHIBITED ARE A FUNCTION OF ROUTE OF EXPOS., AMT. OF SUBST. PRESENT & DURATION OF EXPOSURE; HEALTH EFFECTS RANGE FROM MILD BURNS & PRIMARY IRRITATION TO CORNEAL OPACIFICATION, SEVERE BURNS, NAUSEA, VOMITING (SEE SUPPL DATA)  
Medical Cond Aggravated by Exposure:PRE-EXISTING RESPIRATORY CONDITIONS.

## First Aid

First Aid:SKIN: FLUSH AWAY W/WATER UNTIL "SOAPINESS" IS NO LONGER PRESENT; EYES: IMMEDIATELY FLUSH W/COPIOUS AMTS. OF WATER FOR AT LEAST 15 MINS. IN EITHER CASE, SEEK MEDICAL ATTN.; INHAL: REMOVE TO FRESH AIR - GIVE CPR/O\*2 AS SITUATION DICTATES. ADDITIONAL SUPPORTIVE MEASURES MAY BE REQUIRED; INGEST: IF CONSCIOUS, GIVE PATIENT AS MUCH MILK OR WATER AS POSSIBLE. DO NOT INDUCE VOMITING. GET MED. ATTN. IMMED.

## Fire Fighting

Flash Point:168F/75.6C  
Extinguishing Media:CARBON DIOXIDE, ALCOHOL FOAM, WATER  
Fire Fighting Procedures:NONE CITED  
Unusual Fire/Explosion Hazard:NEVER MIX OR STORE ACIDS, OXIDIZING AGENTS, OR STB(SUPER-TROPICAL BLEACH) TOGETHER W/ DS2; FIRE OR EXPLOSION MAY RESULT.

## Accidental Release

Spill Release Procedures:SPILLS ON POROUS SURFACES(CONCRETE, WOOD, ETC.) SHOULD BE CLEANED & NEUTRALIZED IMMEDIATELY. OTHERWISE, IT WILL BE ABSORBED & BECOME AN INDEFINITE HAZARD. CONTAIN SPILL, NEUTRALIZE, ABSORB ON VERMICULITE, CLAY OR DIATOMACEOUS EARTH. SCOOP UP IN DRUM!  
Neutralizing Agent:SODIUM BISULFATE

## Handling

Handling and Storage Precautions:AVOID EXTREME TEMPERATURES(I.E., 160F/71C) FOR STORAGE! AVOID CONTACT W/LEAKING LIQUID OR VAPOR.  
Other Precautions:SPILL/RELEASE PROCEDURE CONTD: SCOOP UP MATERIAL & CONTAMIN. MATTER, PLACE IN EPOXY COATED DRUM W/REMOVABLE HEAD IAW EPA & DOT RQMTS.; DURING CLEAN-UP, WEAR FULL FACE RESPIR. W/ORGANIC VAPOR CARTRIDGE, ARM-LENGTH RUBBER GLOVES & RUBBER APRON.

## Exposure Controls

Respiratory Protection:FOR DS2 AIRBORNE CONC. FACEPIECE & ONE OF THE FOLLOWING: A) CHEM. CARTRIDGE RESP. W/AMINE CARTRIDGE; B) SUPPL. AIR RESP; C) SUPPL. AIR RESP. IN POSITIVE PRESS. ON CONTIN. FLOW MODE; FOR CONC. >5 PPM OR EMERGENCIES, USE "SCBA"  
Ventilation:LOCAL EXHAUST: NECESSARY IF TLV(TWA) EXCEEDED.  
Protective Gloves:BUTYL RUBBER: ARM'S LENGTH TYPE  
Eye Protection:SPLASHPROOF GOGGLES /FULL FACE SHIELD  
Other Protective Equipment:AS REQUIRED FOR TASK AT HAND; CORROSIVE RESISTANT(I.E. RUBBER) GAUNTLET, BOOTS, & APRON.  
Work Hygienic Practices:USE MATERIAL IAW THE GUIDELINES & INSTRUCTIONS SET FORTH IN USER'S TECH MANUAL.  
Supplemental Safety and Health  
SIGNS & SYMPTOM OVEREXP. CONTD: RESPIRATORY IRRITATION, SKIN SENSITIZATION.

---

## Chemical Properties

HCC:B2

Boiling Pt: =193.3C, 380.F

Spec Gravity: 0.97 - 0.98

pH: >12.5

Appearance and Odor: CLEAR AMBER SOLUTION WITH AMMONIA-LIKE ODOR.

## Stability

Stability Indicator/Materials to Avoid: YES

CORROSIVE: INCOMPATIBLE W/AL, CD, SN, & ZN; LEXAN, CELLULOSE

ACETATE, PVC, MYLAR, ACRYLIC; PAINT, WOOL, OXIDIZING MATRL

Stability Condition to Avoid: EXPOSURE TO AIR. DS2 WILL DETERIORATE IN AIR. EXPOSURE OF 48 HRS OR MORE TO OPEN AIR PRODUCES GELATIN-LIKE BODIES!

Hazardous Decomposition Products: NONE CITED

## Disposal

Waste Disposal Methods: CHOICE OF METHOD DEPENDS ON PHYSICAL CONDITION OF WASTE & FACILITY'S CAPABILITY. FOR EXCESS STOCK, COORDINATE W/LOCAL DRMD; OVERSEAS OPERATE W/IN HOST COUNTRY & DRMD REGS.; /WASTE CORROSIVE (PH >12.5) W/ EPA HAZ. WASTE: D002; INCINERATE OR NEUTRALIZE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.