

NO 600 LINE

MSDS Number

BHCHW

National Stock Number

8010-00N010731

Product Name

NO 600 LINE

Manufacturer

SPECTRA TONE PAINT CORP

Product Identification

Product ID:NO 600 LINE

MSDS Date:01/01/1987

FSC:8010

NIIN:00N010731

MSDS Number: BHCHW

Responsible Party

SPECTRA-TONE PAINT CORPORATION

9635 KLINGERMANN ST.

S.EL MONTE , CA 91733

Emergency Phone: 213-686-1246

Info Phone: 213-686-1246

Cage: 52100

Contractor

SPECTRA-TONE PAINT CORP

SAN BERNADINO, CA 92408-2946

US

800-272-4687/818-442-7269

Cage: 52100

Ingredients

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 1.8%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

LD50 LC50 Mixture:

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SEE SIGNS & SYMPTOMS OF OVEREXPOSURE.

Explanation of Carcinogenicity:N/A FPN

Effects of Overexposure:ACUTE:INHALATION MAY CAUSE HEADACHE &
NAUSEA.SKIN OR EYE CONTACT MAY IRRITATE AS MATERIAL IS SLIGHTLY
ALKALINE,CHRONIC:NONE RECOGNIZED.

First Aid

First Aid:INHALATION:REMOVE TO FRESH AIR.EYES;FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES SKIN:WASH SKIN WITH SOAP AND WATER.INGESTION:IF INGESTED,DRINK LOTS OF WATER TO-DILUTE;DO NOT INDUCE VOMITING.SEE A PHYSICIAN.

Fire Fighting

Flash Point:NON FLAMMABLE

Lower Limits:

Upper Limits:

Extinguishing Media:

Fire Fighting Procedures:FIREFIGHTERS SHOULD BE EQUIPPED WITH SCBA TO PROTECT AGAINST ANY POTENTIALLY TOXIC OR IRRITATING FUMES.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TOEXTREME HEAT,WATER MAY BE HELPFUL IN COOLING UNRUPTURED CONTAINERS.

Accidental Release

Spill Release Procedures:CLEAN UP SPILL IMMEDIATELY BY SOAKING UP WITH CLAY,SAND,ETC.FLUSH WITH WATER.OLACE IN NON-LEAKING CONTAINERS.

Neutralizing Agent:N/K

Handling

Handling and Storage Precautions:STORE IN DRY,WELL VENTILATED PLACE,AWAY FROM EXCESSIVE HEAT.

Other Precautions:AVOID UNNECESSARY CONTACT (SKIN,EYES,ETC.).DO NOT TAKE INTERNALLY.USE WITH ADEQUATE VENTILATION.

Exposure Controls

Respiratory Protection:IF TLV IS EXCEEDED,USE A NIOSH APPROVED RESPIRATOR OR A SCBA.USE MECHANICAL FILTER TO REMOVE SOLID AIRBORNE PARTICLES DURING SPRAY APPLICATION.

Ventilation:GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP EXPOSURE BELOW TLV.

Protective Gloves:NEOPRENE

Eye Protection:CHEM WORK GOGGLES,FACESHLD OPTIONAL

Other Protective Equipment:APRONS,EYE WASHES,SAFETY SHOWERS..

Work Hygienic Practices:OBSERVE GOOD WORK HYGIENIC PRACTICES

Supplemental Safety and Health

BOILING POINT:ESSENTIALLY THAT OF WATER. WT PER GL:10.2.

Chemical Properties

Boiling Pt:B.P. Text:SUP DATA

Melt/Freeze Pt:M.P/F.P Text:

Decomp Temp:Decomp Text:

Vapor Density:HEAV AIR

Spec Gravity:1.226

pH:

Evaporation Rate & Reference:SLOWER THAN ETHER.

Solubility in Water:

Appearance and Odor:

Percent Volatiles by Volume:65

Corrosion Rate:

Stability

Stability Indicator/Materials to Avoid:YES

NONE REASONABLY FORESEEABLE.

Stability Condition to Avoid:

Hazardous Decomposition Products:MAY PRODUCE FUMES EWHEN HEATED TO DECOMPOSITION.MAY RELEASE CO,CO*2,AND OXIDES OF NITROGEN.

Conditions to Avoid Polymerization:

Disposal

Waste Disposal Methods:DISPOSE OF IM ACCORDANCE WITH ALL APPLICABLE LOCAL,STATE,AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.