
MIL-L-6085B/PQ RUST PREVENTIVE 160#0430008

MSDS Number

BHCJL

National Stock Number

9150-00-223-4129

Product Name

MIL-L-6085B/PQ RUST PREVENTIVE 160#0430008

Manufacturer

HULS AMERICA INC

Product Identification

Product ID:MIL-L-6085B/PQ RUST PREVENTIVE 160#0430008

MSDS Date:01/16/1989

FSC:9150

NIIN:00-223-4129

MSDS Number: BHCJL

Responsible Party

HULS AMERICA INC.

TURNER PLACE

PISCATAWAY , NJ 08854

US

Emergency Phone: 201-763-7173

Info Phone: 201-763-7173

Preparer: P.A. PARKER

Cage: 0DH22

Contractor

HULS AMERICA INC

365

PISCATAWAY, NJ 08854-0365

US

908-981-5016

Cage: 0DH22

Ingredients

SULFONIC ACIDS,PETROLEUM,SODIUM SALTS

CAS: 68608-24-4

Fraction By Weight: 100.0%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:LOW ORAL AND DERMAL

TOXICITY;MIST OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE AND SKIN IRRITATION,NAUSEA,VOMITING,RESPIRATORY TRACT IRRITATION.

Explanation of Carcinogenicity:NO DATA AVAILABLE.

Effects of Overexposure:SEE HEALTH HAZARDS DATA.

Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE WORSEN.

First Aid

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES:FLUSH WITH PLENTY OF WATER FOR ABOUT 15-20 MINUTES;SEEK MEDICAL HELP. INHALATION:REMOVE TO FRESH AIR;SEEK MEDICAL HELP. INGESTION:DO NOT INDUCE VOMITING,CALL A PHYSICIAN.

Fire Fighting

Flash Point Method:COC
Flash Point:440F/227C
Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM OR CO*2.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.
Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS;COOL WITH WATER SPRAY.

Accidental Release

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;REMOVE ALL IGNITION SOURCES;CONTAIN FREE MATERIAL;USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:STORE IN COOL, DRY AND WELL VENTILATED AREA;OPERATING TEMPERATURES 440F;DO NOT USE ABOVE THIS TEMPERATURE.

Exposure Controls

Respiratory Protection:NORMALLY NOT NEEDED;IF OVER HEATED;USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE PEL/TLV.
Ventilation:USE LOCAL/GENERAL TO MAINTAIN ADEQUATE CFM.
Protective Gloves:IMPERVIOUS.
Eye Protection:CHEMICAL GOGGLES/FACESHIELD.
Other Protective Equipment:EYE-WASH FOUNTAIN, SAFETY SHOWER.
Work Hygienic Practices:AVOID CONTACT WITH EYES & SKIN;DO NOT BREATHE VAPORS/MIST.
Supplemental Safety and Health

Chemical Properties

HCC:V6
Boiling Pt:B.P. Text:>450F/232C
Vapor Pres:Vapor Density:>1.0
Spec Gravity:Evaporation Rate & Reference:SLOWER THAN BUT ACETATE
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR LIQUID;MILD ODOR.
Percent Volatiles by Volume:NO

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS.
Stability Condition to Avoid:EXTREME HEAT.
Hazardous Decomposition Products:BURNING WILL PRODUCE TOXIC VAPORS,OXIDES OF SULFUR AND CARBON.

Disposal

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES;DISPOSAL MUST BE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.