

ODORLESS SEMI-GLOSS ALKYD ENAMEL ALKYDPAINT

MSDS Number

BHCJV

National Stock Number

6810-00-269-2536

Product Name

ODORLESS SEMI-GLOSS ALKYD ENAMEL ALKYDPAINT

Manufacturer

BIRK PAINT MANUFACTURERS INC

Product Identification

Product ID:ODORLESS SEMI-GLOSS ALKYD ENAMEL ALKYDPAINT

MSDS Date:12/01/1988

FSC:6810

NIIN:00-269-2536

MSDS Number: BHCJV

Responsible Party

BIRK PAINT MANUFACTURERS,INC.

230 KEARNEY AVENUE

JERSEY CITY , NJ 07305

US

Emergency Phone: 201-434-8013

Info Phone: 201-434-8013

Cage: HO453

Contractor

BIRK PAINT MANUFACTURERS,INC.

JERSEY CITY, NJ 07305

US

201-434-8013

Cage: HO453

Ingredients

MINERAL SPIRITS

CAS: 64741-65-7

Fraction By Weight: 23.0%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

OTHER COMPONENTS (TYPE NOT SPECIFIED)

Fraction By Weight: BALANCE

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:IRRITATION OF

EYES,SKIN,RESPIRATORY AND G.I. SYSTEM,CNS EFFECTS LIKE

HEADACHE,DIZZINESS,WEAKNESS,FATIGUE,NAUSEA,HEADACHE,POSSIBLE

UNCONSCIOUSNESS OR ASPHYXIATION,NAUSEA,VOMITING,DIARRHEA IN CASE

OF INGESTION,REDNESS OR TEARING OF EYESOR DRYING OR DEFATTING OF SKIN. CHRONIC:DERMATITIS,RESPIRATORY PROBLEM.

Explanation of Carcinogenicity:DATA PER MSDS.

Effects of Overexposure:SEE HEALTH HAZARDS DATA.

Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE WORSEN.

First Aid

First Aid:SKIN AND EYES:FLUSH WITH PLENTY OF WATER FOR ABOUT 15-20 MINUTES;SEEK MEDICAL HELP AS SOON AS POSSIBLE. INHALATION:REMOVE TO FRESH AIR,CALL A PHYSICIAN IF NEEDED. INGESTION:DO NOT INDUCE VOMITING;CALL A PHYSICIAN IMMEDIATELY.

Fire Fighting

Flash Point:100F/38C

Lower Limits:1.0

Extinguishing Media:DRY CHEMICAL,CO*2,FOAM.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.

Unusual Fire/Explosion Hazard:AVOID EXTREME HEAT;CAN IGNITE EXPLOSIVELY.

Accidental Release

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;REMOVE ALL IGNITION SOURCES;CONTAIN FREE LIQUID IF POSSIBLE. USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT,OPEN FLAMES.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE PEL/TLV.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:NEOPRENE.

Eye Protection:CHEMICAL GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING,EYE-WASH FACILITIES.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS/MIST;WASH THOROUGHLY AFTER EACH USE;DO NOT SMOKE IN WORK AREA.

Supplemental Safety and Health

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:355-400F

Vapor Pres:4.0

Vapor Density:>1.0;AIR=1

Spec Gravity:1.32

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:ODORLESS SEMI-GLOSS ALKYD PAINT.

Percent Volatiles by Volume:23.0

Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZERS,ACIDS,BASES & SELECTED AMINES.

Stability Condition to Avoid:EXTREME HEAT,SHOCK FROM DROPPING.

Hazardous Decomposition Products:CO*2,CO,VARIOUS HYDROCARBONS.

Disposal

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.