

LOCTITE FORM-A-THREAD STRIPPED THREAD REPAIR

MSDS Number

BHCRL

National Stock Number

6850-00B120061

Product Name

LOCTITE FORM-A-THREAD STRIPPED THREAD REPAIR

Manufacturer

LOCTITE CORP AUTOMOTIVE AND CONSUMER GROUP

Product Identification

Product ID:LOCTITE FORM-A-THREAD STRIPPED THREAD REPAIR MSDS Date: 02/02/1986 FSC:6850 NIIN:00B120061

MSDS Number: BHCRL **Responsible Party**

LOCTITE CORP AUTOMOTIVE AND CONSUMER GROUP

4450 CRANWOOD COURT

CLEVELAND , OH 44128-4004

US

Emergency Phone: 1-800-321-9188

Info Phone: 216-475-3600 Preparer: ROBERT J. CARTER

Cage: 08028 **Contractor**

LOCTITE CORPORATION

ROCKY HILL, CT 06067-3910

US

860-571-5100 Cage: 05972

Ingredients

ALUMINUM (SARA III)

CAS: 7429-90-5 RTECS: BD0330000

Fraction By Weight: 30-35%

OSHA PEL15MG/M3 DUST/5 FUME ACGIH TLV: 10MG/M3 DUST; 9192

PIGMENT

Fraction By Weight: SILICON DIOXIDE CAS: 60676-86-0 RTECS: VV7320000



Fraction By Weight:

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

BISPHENOL A DIMETHACRYLATE

Fraction By Weight: 60-65%

HETEROCYCLIC METHACRYLATE MONOMER

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic: INHALATION OF PURE SILICON DIOXIDE DUST HAS BEEN SHOWN TO CAUSE PULMONARY EFFECTS. WITH PROPER PRECAUTIONS, NORMAL USE OF THIS PRODUCT SHOULD POSE NO SUCH HAZARD. MILD SKIN IRRITANT. Effects of Overexposure: MAY CAUSE IRRITATION ON PROLONGED CONTACT IN

SENSITIVE INDIVIDUALS.

First Aid

First Aid:INGESTION-DO NOT INDUCE VOMITING. KEEP INDIVIDUAL CALM. OBTAIN MEDICAL ATTENTION, INHALATION-REMOVE TO FRESH AIR. SKIN-FLUSH WITH WATER. EYES-FLUSH WITH WATER FOR 15 MINUTES. OBTAIN MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:CC Flash Point:>200F Extinguishing Media: CO2, FOAM, DRY CHEMICAL. Unusual Fire/Explosion Hazard: NONE KNOWN.

Accidental Release

Spill Release Procedures: SOAK UP IN SAND, SILICO OR INERT ABSORBENT.

Handling

Handling and Storage Precautions: AVOID PROLONGED SKIN CONTACT. KEEP AWAY FROM EYES. OBSERVE NORMAL SAFETY PRECAUTIONS.

Exposure Controls

Ventilation: FOR PROLONGED USE. Protective Gloves: NOT NEEDED FOR NORMAL USE. Eye Protection: NOT NEEDED FOR NORMAL USE. Supplemental Safety and Health

Chemical Properties

Spec Gravity: 1.40 @ 77F Solubility in Water: INSOLUBLE

Appearance and Odor: GRAY LIQUID, MILDLY PUNGENT ODOR.

Stability

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products: OXIDES OF CARBON FORMED BY FIRE OR THERMAL DECOMPOSITION.

Disposal

Waste Disposal Methods: LANDFILL OR INCINERATE ACCORDING TO EPA OR LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department



of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.