

LACQUER SPRAY PAINT GRAY 16099 IF IB 2671

MSDS Number

BHCXY

National Stock Number

8010-00-151-2958

Product Name

LACQUER SPRAY PAINT GRAY 16099 IF IB 2671

Manufacturer

ILLINOIS BROZE PAINT

Product Identification

Product ID:LACQUER SPRAY PAINT GRAY 16099 IF IB 2671

MSDS Date:01/01/1980

FSC:8010

NIIN:00-151-2958

MSDS Number: BHCXY

Responsible Party

ILLINOIS BROZE PAINT

300 E. MAIN STREET

LAKE ZURICH , IL 60047

US

Emergency Phone: 312-359-6433

Info Phone: 312-438-8201

Cage: JO997

Contractor

ILLINOIS BROZE PAINT

NA

LAKE ZURICH, IL 60047

US

312-438-8201 OR 312-359-6433

Cage: JO997

Ingredients

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 37.3%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

2-BUTOXYETHANOL

CAS: 111-76-2

RTECS: KJ8575000

Fraction By Weight: 1.0%

OSHA PELs, 50 PPM

ACGIH TLV: S, 25 PPM; 9293

MINERAL SPIRITS

Fraction By Weight: 1.7%

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 0.3%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 1.7%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 0.3%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

VM &P NAPHTHA

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 11.0%

PROPANE/ISOBUTANE

CAS: 68476-86-8

Fraction By Weight: 32.0%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM. DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUS OR COMA. SKIN OR EYE: PRIMARY IRRITANT

First Aid

First Aid:INHAL: REMOVE TO FRESH AIR, RESTORE BREATHING. TREAT SYMPTOMATICALLY. CONSULT A PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MIN. TAKE TO PHYSICIAN. SKIN: WIPE OFF WITH TOWEL. REMOVE REMAINDER WITH MINERAL SPIRITS, TURPENTINE, OR LACQUER THINNER. WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING.

Fire Fighting

Flash Point:NR
Lower Limits:0.8
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Unusual Fire/Explosion Hazard:CANS WILL RUPTURE FROM INTERNAL PRESSURE AT ABOUT 190 F AND DISCHARGE FLAMMABLE CONTENTS. WHEN HEATED TO DECOMPOSITION, TOXIC FUMES ARE FORMED

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES & ELECTRICAL, ETC.) AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT

Handling

Handling and Storage Precautions:DON'T STORE ABOVE 120 F. STORE LARGE QUANTITIES IN BLEED-PROTECTED & PROTECTED FOR STORAGE OF NFPA CLASSIA FLAMMABLE LIQUIDS
Other Precautions:DO NOT SPRAY IN EYES. DO NOT PUNCTURE OR INCINERATE CANS. DO NOT STICK PIN OR ANY SHARP OBJECTS INTO OPENING ON TOP OF CAN. FINGER MUST NOT PROTRUDE OVER SPRAY BUTTON

Exposure Controls

Respiratory Protection:CASUAL USE NONE REQUIRED. PROVIDED VENTILATION IS AVAILABLE AS OUTLINED BELOW: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF MOST HAZARDOUS INGREDIENT BELOW ACCEPTABLE LIMITS
Ventilation:LOCAL EXHAUST VENTILATION TO KEEP TLV LIMIT MINIMUM
Protective Gloves:NONE
Eye Protection:NO SPECIAL PROTECTION REQUIRED
Other Protective Equipment:NONE
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:42-391 F
Vapor Density:> AIR
Percent Volatiles by Volume:89

Stability

Stability Indicator/Materials to Avoid:YES
NK
Hazardous Decomposition Products:HYDROGEN CHLORIDE, CARBON MONOXIDE, PHOSGENE

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.