

THINNER,SYNTHETIC RESIN ENAMEL

MSDS Number

BHCYF

National Stock Number

8010-00-160-5794

Product Name

THINNER,SYNTHETIC RESIN ENAMEL

Manufacturer

CSD INC (OBSOLETE ADDRESS USE 4N760)

Product Identification

Product ID:THINNER,SYNTHETIC RESIN ENAMEL

MSDS Date:07/01/1988

FSC:8010

NIIN:00-160-5794

MSDS Number: BHCYF

Responsible Party

CSD INC. (OBSOLETE ADDRESS; USE 4N760)

420 SEABOARD DRIVE

MATTHEWS , NC 28105-5073

US

Emergency Phone: 704-821-9822

Info Phone: 704-821-9822

Cage: 5W216

Contractor

MATHEWS, INC)

MATTHEWS, NC 28105-5073

US

704-821-9822

Cage: 5W216

Ingredients

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 20-22%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 50-57%

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9192

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 14-16%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOBUTYL ISOBUTYRATE

CAS: 97-85-8

RTECS: NQ5250000

Fraction By Weight: 9-12%

Hazards

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS, LIVER, KIDNEY. ACUTE- MAY CAUSE SEVERE EYE IRRITATION. INHALATION MAY CAUSE CNS DEPRESSION. MAY BE ABSORBED THROUGH SKIN. MAY CAUSE DEFATTING. INGESTION CAN BE HARMFUL. A SPIRATION HAZARD. CHRONIC- MAY CAUSE DERMATITIS, LIVER, KIDNEY INJURY, BRAIN & CNS DAMAGE. Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, LOSS OF COORDINATION, SEVERE EYE IRRITATION, REDNESS AND ITCHING OR BURNING SENSATION OF EYES OR SKIN, ABDOMINAL PAIN, WEAKNESS, CONFUSION, DIARRHEA, BREATHING DIFFICULTY.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED LIVER, KIDNEY, CNS, BRAIN OR RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. CALL PHYSICIAN. SKIN:WASH WITH SOAP & WATER . ORAL:DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY. PHYSICIAN SHOULD CONSULT POISON CONTROL CENTER AT 212-664-2121 (VOMITING). NEVER GIVE ANYTIHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Fire Fighting

Flash Point Method:TCC

Flash Point:50.0F,10.0C

Lower Limits:0.9%

Upper Limits:NOT GIVEN

Extinguishing Media:USE CARBON DIOXIDE, SAND, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL

CONSIDERABLE DISTANCE OR BE MOVED BY VENTILATION TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINER MAY EXPLODE.

Accidental Release

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. CONTAIN SPILL. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH OR VERMICULITE. GROUND ALL HANDLING EQUIPMENTS. PREVENT LIQUID FROM ENTERING SEWERS.

Neutralizing Agent:NOT RELEVANT

Handling

Handling and Storage Precautions:STORE IN COOL PLACE, AWAY FROM SOURCES OF IGNITION & STRONG OXIDIZING AGENTS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:EMPTY CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS. DO NOT RE-USE CONTAINER. AVOID BREATHING VAPO RS OR MISTS.

Exposure Controls

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR OR SELF CONTAINED BREATHING APPARATUS, WITH A FULL FACE PIECE, OPERATED IN POSITIVE PR ESSURE MODE.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:COTTON LINED NEOPRENE

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER, INDUSTRIAL-TYPE WORK CLOTHING TO PROTECT SKIN

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKING/SMOKING.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:F2

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:230F,110C

Melt/Freeze Pt:M.P/F.P Text:>-20F,>-29C

Vapor Pres:22

Vapor Density:3.0

Spec Gravity:0.792

Solubility in Water:5-10%

Appearance and Odor:CLEAR LIQUID WITH CHARACTERISTIC ODOR

Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:MAY FORM CARBON MONOXIDE, CARBON DIOXIDE.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.