

## **PRMR COATING SYNTHETIC RUST INHIBIT.LAC.RES**

### **MSDS Number**

BHCYK

### **National Stock Number**

8010-00-161-7275

### **Product Name**

PRMR COATING SYNTHETIC RUST INHIBIT.LAC.RES

### **Manufacturer**

CON LUX COATINGS INC

### **Product Identification**

Product ID:PRMR COATING SYNTHETIC RUST INHIBIT.LAC.RES

MSDS Date:10/25/1983

FSC:8010

NIIN:00-161-7275

MSDS Number: BHCYK

### **Responsible Party**

CON-LUX COATINGS, INC.

TALMAGDE ROAD

EDISON , NJ 08818

US

Emergency Phone: 201-287-4000

Cage: 60189

### **Contractor**

CON-LUX COATINGS INC

847

EDISON, NJ 08818-0847

US

732-287-4000

Cage: 60189

### **Ingredients**

ZINC CHROMATE

CAS: 13530-65-9

RTECS: GB3290000

Fraction By Weight: 4.2%

OSHA PEL0.1 MG/M3 (CRO3)

ACGIH TLV: 0.01MG/M3(CR)A1;9192

VM&P NAPHTHA

CAS: 64742-89-8

Fraction By Weight: 28.1%

ACGIH TLV: 500 PPM

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 9.8%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Effects of Overexposure:IRRITATION OF EYES AND SKIN MAY OCCUR WITH  
OVEREXPOSURE. CONTINUE BREATHING VAPORS, IN SOME INSTANCES, MAY  
IRRITATE RESPIRATORY TRACT AND CAUSE DIZZINESS, WHICH IS NORMAL  
FOR SOLVENT BASE PRODUCT S.

## First Aid

First Aid:FLUSH SKIN AND EYE CONTACT WITH PLENTY OF WATER. IF INHALED,  
REMOVE TO FRESH AIRIF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

## Fire Fighting

Flash Point Method:TCC  
Flash Point:50F 10C  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER MIST  
Fire Fighting Procedures:SMOTHER FLAMES WITH ONE OF THE ABOVE  
EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED  
CONTAINERS IN VICINITY.  
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT. DO NOT USE IN  
AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
PROLONGED BREATHING OF VAPORS. VENTILATE AREA. CLEAN UP  
WITHABSORBENT MATERIAL.

## Handling

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED AND  
PROTECTED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS.  
Other Precautions:STORE IN BUILDINGS DESIGNED AND PROTECTED FOR  
STORAGE OF NFPA CLASS II FLAMMABLLIQUIDS.

## Exposure Controls

Respiratory Protection:IN OPEN AREAS USE NATIONAL INSTITUTE FOR  
OCCUPATIONAL SAFETY AND HEALTH APPROVEDFILTER RESPIRATOR. IN  
CONFINED AREAS USE OCCUPATIONAL SAFETY AND HEALTH APPROVEDCHEMICAL  
FILTERS.  
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION.  
Protective Gloves:REQUIRED FOR LONG/REPEATED EXPOSURE  
Eye Protection:USE SAFETY EYEWEAR  
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH  
CONTAMINATED CLOTHING.  
Supplemental Safety and Health  
NK

## Chemical Properties

Boiling Pt:B.P. Text:243 - 245F  
Vapor Density:> AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:64.6

## Stability

Stability Indicator/Materials to Avoid:YES

NK

Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH STATE, LOCAL AND FEDERAL REGULATIONS. DO NOT INCINERATE UNOPENED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.