
CLEAR GLOSS LACQUER ID 797804

MSDS Number

BHCYT

National Stock Number

8010-00-166-1689

Product Name

CLEAR GLOSS LACQUER ID 797804

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID: CLEAR GLOSS LACQUER ID 797804

MSDS Date: 12/15/1988

FSC: 8010

NIIN: 00-166-1689

MSDS Number: BHCYT

Responsible Party

PRATT & LAMBERT, INC.

WICHITA , KS 67201

US

Emergency Phone: 316-733-1361

Info Phone: 316-733-1361

Preparer: W.A. ELLISON

Cage: FO127

Contractor

PRATT AND LAMBERT INC

22

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: YES IARC: NO OSHA: NO
Health Hazards Acute and Chronic: SWALLOWING: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING. ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHALATION: MAY CAUSE NOSE, THROAT IRRITATION. EYE: MAY CAUSE EYE IRRITATION. SKIN: PRIMARY SKIN IRRITANT. MAY CAUSE DEFATTING AND IRRITATION OF THE SKIN.

Explanation of Carcinogenicity: DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS A POTENTIAL CARCINOGEN BY THE NTP. OVEREXPOSURE TO TOLUENE MAY CAUSE LIVER DAMAG

Effects of Overexposure: PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

First Aid

First Aid:SWALLOWING: DO NOT INDUCE VOMITING. GET MED ATTN: INHALATION: REMOVE TO FRESH AIR IMMED. IF BREATHING HAS STOPPED GIVE CPR. GET MED ATTN: EYE: FLUSH WITH LARGE AMOUNTS OF WATER LIFTING UPPER AND LOWER LIDS FOR 15 MIN. SKIN: IMMEDIATELY FLUSH WITH WATER/REMOVE CONTAMINATED CLOTHING AS WATER IS APPLIED CONSULT A M.D.

Fire Fighting

Flash Point:20F / -6.67C
Extinguishing Media:CLASS B FIRE EXTINGUISHERS TO EXTINGUISH FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE WATER TO COOL EXPOSED CONTAINERS TOPREVENT PRESSURE BUILD-UP AND POSSIBLE EXPLOSION. FOG NOZZLE PREFERRED W/WATER.
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE HEALTH HAZARD. OBTAIN MEDICAL ATTENTION. WARNING FLAMMABLE.

Accidental Release

Spill Release Procedures:USE APPROPRIATE RESPIRATORS FOR SIZE OF SPILL. ELIMINATE ALL IGNITION SOURCES. DIKE AND CONTAIN SPILLS WITH INERT MATERIAL. TRANSFER AND RECOVER IN METAL CONTAINERS. USE ONLY NON-SPARKING TOOLS. DO NOT CONTAMINATE WATER SOURCES.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:DO NOT TAKE INTERNALLY. CLOSE AFTER USE. DO NOT RE-USE FOR ANY PURPOSE. CONTAINERS S/BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD/BRAZE/CUT ONEMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM NOT A PRESSURE VESSEL.

Exposure Controls

Respiratory Protection:GENERAL EXPOSURE MAY NOT REQUIRE THE USE OF RESPIRATORY PROTECTION. RESTRICTED VENTILATION AREAS A NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR MAY BE REQUIRED. CONDITIONS SUCH AS SPRAYING A MECHANICAL PREFILTER MAY BE REQUIRED.
CONFINED
Ventilation:GENERAL DILUTION AND LOCAL EXHAUSE VENTILATION TO MAINTAIN HAZ SUBSTANCES BELOW LOWEST EXPOSURE LIMITS.
Protective Gloves:SOLVENT IMPERMEABLE GLOVES
Eye Protection:SAFETY SPECTACLES
Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.
Work Hygienic Practices:NOT LIKELY TO BE NEEDED.
Supplemental Safety and Health
RESPIRATION PROTECTION CONTINUED: AREAS USE A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Chemical Properties

Boiling Pt:B.P. Text:180 TO 302F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:85

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.
Hazardous Decomposition Products:WILL NOT OCCUR
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND FLAME.

Disposal

Waste Disposal Methods:DISPOSE IAW FED/ST/LO LAWS. INCINERATE ONLY IN EPAFACILITY. CONTAMINATED ABSORBANT MAY BE DISPOSED IN A HAZARDOUS

WASTE LANDFILL. RCRA CLASSIFICATION D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.