

CARTER'S RUBBER CEMENT

MSDS Number

BHDFB

National Stock Number

8040-00-262-9040

Product Name

CARTER'S RUBBER CEMENT

Manufacturer

DENNISON STATIONERY PRODUCTS COMPANY

Product Identification

Product ID: CARTER'S RUBBER CEMENT

MSDS Date: 07/19/1988

FSC: 8040

NIIN: 00-262-9040

MSDS Number: BHDFB

Responsible Party

DENNISON STATIONERY PRODUCTS COMPANY

300 HOWARD STREET

FRAMINGHAM , MA 01701

US

Emergency Phone: 508-879-0511 X4636

Cage: HO918

Contractor

DENNISON STATIONARY PRODUCTS CO

FARMINGTON, MA 01701

US

508-879-0511

Cage: HO918

Ingredients

SOLVENT NAPHTHA

CAS: 67472-89-8

Fraction By Weight: 88.6%

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: OVEREXPOSURE CAN LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION PRODUCING HEADACHES, DIZZINESS, NAUSEA, AND LOSS OF CONSCIOUSNESS.

Effects of Overexposure: HEADACHES, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS.

Medical Cond Aggravated by Exposure: SKIN DISEASE, CHRONIC RESPIRATORY DISEASE

First Aid

First Aid: EYES: FLUSH WITH WATER, CALL PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. CALL PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. LAUNDER CLOTHING. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL

ATTENTION.

Fire Fighting

Flash Point Method:TCC

Flash Point:< 10F/-24C

Lower Limits:7.0

Upper Limits:1.1

Extinguishing Media:CO2, FOAM, DRY CHEMICAL, WATER FOG OR SPRAY

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING INCLUDING NIOSH SELF-CONTAINED BREATHING APPARATUS COOL EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:IN CASE OF LARGE FIRES, ALSO COOL SURROUNDING EQUIPMENT AND STRUCTURES WITH WATER. DO NOT MIX WITH STRONG OXIDANTS.

Accidental Release

Spill Release Procedures:AVOID OPEN FLAMES OR SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. ADD ABSORBANT (SAWDUST, SANDETC.) TO SPILL AREA. TO AVOID SPILLING, DEEP CAP TIGHTLY CLOSED WHEN NOT USING.

Handling

Handling and Storage Precautions:AVOID OPEN FLAMES, SPARK SOURCES, SPLASH SPILLING, EXCESSIVE HEAT. KEEP CONTAINERS CLOSED WHEN NOT USING.

Other Precautions:CAREFULLY READ ALL DIRECTIONS AND CAUTIONS ON PRODUCT CONTAINER.

Exposure Controls

Ventilation:LOCAL EXHAUST IF NEEDED TO CONTROL VAPOR. MECHANICAL (GEN) VENTILATION EXPLOSION PROOF EQUIPMENT.

Protective Gloves:PVA OR NITRILE RUBBER

Eye Protection:SAFETY GLASSES/GOGGLES

Work Hygienic Practices:WASH HANDS BEFORE EATING, DO NOT SMOKE OR USE NEAR OPEN FLAME.

Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:151 - 225F

Vapor Pres:250 @ 100F

Vapor Density:3.3

Spec Gravity:.72

Evaporation Rate & Reference:5.8 (BUTYL ACETATE = 1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BUFF COLOR LIQUID WITH HYDROCARBON ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS LIKE CHLORINE

Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

Disposal

Waste Disposal Methods:EVAPORATE AND PEEL RESIDUE FROM SURFACE. TREAT AS HYDROCARBON.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.