

FAMOWOOD, 303600010

MSDS Number

BHDFC

National Stock Number

8010-00-262-9172

Product Name

FAMOWOOD, 303600010

Manufacturer

BEVERLY MANUFACTURING COMPANY

Product Identification

Product ID:FAMOWOOD, 303600010

MSDS Date:11/16/1987

FSC:8010

NIIN:00-262-9172

MSDS Number: BHDFC

Responsible Party

BEVERLY MANUFACTURING COMPANY

9118 S MAIN ST

LOS ANGELES , CA 90003-3723

US

Preparer: TIM AYERS

Cage: DO074

Contractor

BEVERLY MFG CO

LOS ANGELES, CA 90003-3723

US

213-755-8564

Cage: 21766

Ingredients

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 10 - 20%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 10 - 20%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight:

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

VM&P NAPHTHA

CAS: 64742-89-8

Fraction By Weight: 5%

OSHA PEL200 PPM

ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EARLY TO MODERATE CENTRAL NERVOUS
SYSTEM DEPRESSION MAY BE EVIDENCED BY GIDDINESS, DIZZINESS,
AND NAUSEA, IN EXTREME CASES, UNCONSCIOUSNESS & DEATH.
Effects of Overexposure:INHAL:HIGH VAPOR CONCENT. MAY PRODUCE CENTRAL
NERVOUS SYSTEM DEPRESSION. SKIN:MILDLY IRRITATING,
PROLONGED/REPEATED LIQ CONTACT CAN RESULT IN DEFATTING, &
DERMATITIS. EYE: LIQUID SEVERLY IRRITA TING.HIGH VAPOR CONCENT.
ALSO IRRITATINGST: MAY PRODUCE CENTRAL NERVOUS SYSTEM
DEPRESSION.
Medical Cond Aggravated by Exposure:MAY AGGRAVATE PRE EXISTING LIVER OR
KIDNEY DISEASE

First Aid

First Aid:EYE:IMMEDIATELY FLUSH W/WTR FOR 15 MINS. WHILE HOLDING EYE
LIDS OPEN.GET MEDICALATTENTION. SKIN:FLUSH W/WATER,IF IRRITATION
OCCURS GET MEDICAL ATTENTION. INHAL:REMOVE VICTIM TO FRESH
AIR & PROVI DE OXYGEN IF BRATHING IS DIFFICULT. GETMEDICAL
ATTENTION. INGEST: DONOT GIVE LIQ. IF UNCONSCIOUS/VERY DROWSY.
OTHERWISEGIVE 2 GLS OF WTR & INDUCE VOMITING.KEEP HEAD BELOW HIPS.
GET MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:TCC
Flash Point:-15F/-26C
Lower Limits:12.8
Upper Limits:1.0
Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:EXTREMELY FLAMMABLE. EVACUATE ALL PERSONNEL.
DONOT ENTER CONFINED SPACE W/O FULLBUNKER GEAR. INCLUDING A
POSITIVE PRESSURE S.C.B.A.,COOL FIRE EXPSD CONTNR W/WTR
Unusual Fire/Explosion Hazard:CONTAINRS EXPOSED TO INTENSE HEAT FROM
FIRES SHOULD BE COOLED W/WATER TO PREVENTVAPOR PRESSURE BUILD UP
WHICH COULD RESULT IN CONTAINER RUPTURE.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. HANDLING
EQUIP. MUST BE GROUNDED TO PREVENT SPARKING. PLACE IN NONLEAKING

CONTAINERS FOR PROPER DISPOSAL. EXTREMELY FLAMMABLE.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS,& FLAMES.
VAPORS MAY ACCUMULATE & TRAVEL TO IGNITION SOURCES.KEEP
CONTAINERS CLSD WHEN NOT IN USE.USE ADEQUATE VENTILATN
Other Precautions:EMPTY CONTAINERS CAN CONTAIN EXPLOSIVE VAPORS. DONOT
CUT,DRILL,GRIND,WELD, NEAR OR ON CONTAINERS. GROUND FIXED
EQUIPMENT. BOND AND GROUND TRANSFER CONTAINERS & EQUIPMENT.

Exposure Controls

Respiratory Protection:NIOSH APPROVED RESPIRATOR TO PREVENT
OVEREXPOSURE. IN ACCORDANCE WITH 29 CFR 1910.134. USE EITHER AN
ATMOSPHERE SUPPLYING RESPIRATOR OR AN AIR PURIFYING RESPIRATOR
FOR ORGANIC VAPORS.
Ventilation:EXPLOSION PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR
CONCENTRATIONS
Protective Gloves:RUBBER OR VINYL COATED
Eye Protection:CHEMICAL GOGGLES
Other Protective Equipment:WEAR IMPERVIOUS CLOTHING. EYEWASH FOUNTAINS
AND SAFETY SHOWERS SHOULD BE EASILY ACCESSIBLE.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING,DRINKING,ORSMOKING.
Supplemental Safety and Health
NK

Chemical Properties

HCC:F2
Boiling Pt:B.P. Text:133-206F
Vapor Density:> AIR
Spec Gravity:1.5
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NIL
Appearance and Odor:COLORED PASTE APPEARANCE WITH SOLVENT ODOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, ALKALINE MATERIALS, AND STRONG COMPOUNDS.
Stability Condition to Avoid:HEAT,SPARKS,FLAME, AND PREVENT VAPOR
ACCUMULATION.
Hazardous Decomposition Products:CARBON MONOXIDE, OXIDES OF NITROGEN
AND UNIDENTIFIED ORGANICCOMPOUNDS.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE, AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.