

WAX GEN PURPOSE, SOLVENT, PASTE WAX

MSDS Number

BHDFQ

National Stock Number

7930-00-266-7128

Product Name

WAX GEN PURPOSE, SOLVENT, PASTE WAX

Manufacturer

INDUSTRIAL FLOOR FINISHES

Product Identification

Product ID:WAX GEN PURPOSE, SOLVENT, PASTE WAX

MSDS Date:07/01/1988

FSC:7930

NIIN:00-266-7128

MSDS Number: BHDFQ

Responsible Party

INDUSTRIAL FLOOR FINISHES

605 SPRINGS RD

BEDFORD , MA 01730

US

Emergency Phone: 1-800-424-9300

Info Phone: 609-667-5161

Preparer: T. PITROLFFY

Cage: INDUS

Contractor

INDUSTRIAL FLOOR FINISHES

BEDFORD, MA 01730

US

1-617-667-5161

Cage: INDUS

Ingredients

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: < 80%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:YES

Health Hazards Acute and Chronic:ACUTE: CAUSES EYE IRRITATION, DRYING OF SKIN, HEADACHE, DIZZINESS, NAUSEA, VAPORS MAY BE NARCOTIC.

CHRONIC: RESPIRATORY TRACT IRRITATION, COULD DAMAGE LIVER AND KIDNEY

Effects of Overexposure:DIZZY FEELING, IRRITATION AND REDNESS OF SKIN, PALE AND NAUSEOUS

Medical Cond Aggravated by Exposure:KIDNEY, LIVER AND LUNG PROBLEMS

First Aid

First Aid:EYES & SKIN: FLUSH WITH PLENTY OF WATER. INHALATION: REMOVE TO FRESH AIR BEGIN CPR IF NEEDED. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION

Fire Fighting

Flash Point Method:TCC
Flash Point:102 F 38.89 C
Lower Limits:6.0
Upper Limits:0.7
Extinguishing Media:CO2, FOAM, DRY-CHEMICAL
Fire Fighting Procedures:COOL CONTAINERS WITH WATER SPRAY
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST, IF EXPOSED TO EXTREME HEAT. ISOLATE FROM HEAT AND SPARKS.

Accidental Release

Spill Release Procedures:PICK UP SPILLED MATERIAL INTO METAL CONTAINER. AVOID SPARKS, FLAME, HOT SURFACES. WIPE OFF RESIDUE WITH RAG.

Handling

Handling and Storage Precautions:COMBUSTIBLE, KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME, USE ADEQUATE VENTILATION, AVOID PROLONGED OR REPEATED CONTACT KEEP CONTAINERS CLOSED.
Other Precautions:STORE IN SECURE AREA. DISPOSE OF EMPTY CONTAINERS SAFELY. KEEP AWAY FROM CHILDREN.

Exposure Controls

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV LIMITS
Ventilation:LOCAL RECOMMENDED & MECHANICAL ASSURE FRESH AIR CIRCULATION
Protective Gloves:RUBBER RECOMMENDED
Eye Protection:GOGGLES RECOMMENDED
Other Protective Equipment:NA
Work Hygienic Practices:DO NOT EAT, DRINK NEXT TO MATERIAL, WASH HANDS, FACE AFTER WORK
Supplemental Safety and Health
NK

Chemical Properties

HCC:F8
Boiling Pt:B.P. Text:311-370 F
Melt/Freeze Pt:M.P/F.P Text:120 F
Vapor Pres:2
Vapor Density:4.7
Spec Gravity:0.758
Evaporation Rate & Reference:0.21
Solubility in Water:NEGLIGIBLE
Appearance and Odor:PLIABLE PASTE, SLIGHT SOLVENT ODOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAME
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE

Disposal

Waste Disposal Methods:INCINERATE OR USE SANITARY LANDFILL FOR CONTAMINATED RESIDUE. ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.