

METAL POLISH

MSDS Number

BHDFR

National Stock Number

7930-00-266-7137

Product Name

METAL POLISH

Manufacturer

INDUSTRIAL FLOOR FINISHES

Product Identification

Product ID:METAL POLISH

MSDS Date:05/01/1987

FSC:7930

NIIN:00-266-7137

MSDS Number: BHDFR

Responsible Party

INDUSTRIAL FLOOR FINISHES

605 SPRING STREET

BEDFORD , MA 01730

US

Emergency Phone: 617-667-5161 OR LOCAL POISON CENTER

Preparer: T. PITROLFFY

Cage: INDUS

Contractor

PEMATEX INDUSTRIAL CORPORATION

AVON, CT 06001

US

1-617-667-5161

Cage: PERMA

Ingredients

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 17%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRIMARY EYE & SKIN IRRITANT WITH CONTACT. INHALATION: MAY CAUSE HEADACHE, DIZZINESS & NAUSEA.

CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV

Effects of Overexposure:PRIMARY EYE & SKIN IRRITANT WITH CONTACT.

INHALATION: MAY CAUSE HEADACHE, DIZZINESS & NAUSEA. CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV

First Aid

First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH SOAP & WATER, APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR, RESTORE BREATHING, CALL PHYSICIAN. AND INGESTION: DRINKWATER OR MILK, DO NOT INDUCE VOMITING. C ALL POISON CONTROL.

Fire Fighting

Flash Point Method:TCC
Flash Point:MIN 104 F 40.00C
Lower Limits:0.8
Upper Limits:6.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG
Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP OR AUTO-IGNITION
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION, SPRINKLE WITH ABSORBENT. FOG WITH WATER FLUSH/SCRAPE INTO RETAINING AREAOR CONTAINER. INCREASE VENTILATION. AVOID BREATH- ING VAPORS.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. USE ADEQUATE VENTILATION AVOID PROLONGED OR REPEATED CONTACT. KEEP CONTAINER CLOSED.
Other Precautions:AVOID STATIC BUILD-UP. KEEP AWAY FROM CHILDREN.

Exposure Controls

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV
Ventilation:LOCAL EXHAUST, MECHANICAL EXHAUST FROM LOWER LEVELS
Protective Gloves:USE RUBBER GLOVES
Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYE BATH, SAFETY SHOWER, AND PROTECTIVE CREAM
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:215
Vapor Pres:2
Vapor Density:2.8
Spec Gravity:1.1
Evaporation Rate & Reference:0.8
Solubility in Water:PARTIAL
Appearance and Odor:PINK CREAMY LIQUID, AMMONIA ODOR
Percent Volatiles by Volume:74

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME AND FIRE
Hazardous Decomposition Products:THERMAL DECOMPOSTION PRODUCES FUMES THAT MAY YIELD CARBON MONOXIDE

Disposal

Waste Disposal Methods:INCINERATE OR DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS. EMPTY CONTAINERS MAY RETAIN FUMES. DO NOT EXPOSE TO HEAT OR FLAME

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.