

WAX GENERAL PURPOSE SOLVENT TYPE PASTE WAX

MSDS Number

BHDFV

National Stock Number

7930-00-267-4928

Product Name

WAX GENERAL PURPOSE SOLVENT TYPE PASTE WAX

Manufacturer

INDUSTRIAL FLOOR FINISHES

Product Identification

Product ID:WAX GENERAL PURPOSE SOLVENT TYPE PASTE WAX MSDS Date:07/01/1988 FSC:7930 NIIN:00-267-4928

MSDS Number: BHDFV **Responsible Party**

INDUSTRIAL FLOOR FINISHES

605 SPRINGS RD

BEDFORD, MA 01730

US

Emergency Phone: 1-800-424-9300 HEALTH POISON CENTER

Info Phone: 617-667-5161 Preparer: T. PITROLFFY

Cage: INDUS

Contractor

PEMATEX INDUSTRIAL CORPORATION

AVON, CT 06001

US

1-617-667-5161

Cage: PERMA Ingredients

STODDARD SOLVENT

CAS: 8052-41-3 RTECS: WJ8925000 Fraction By Weight: OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:YES
Health Hazards Acute and Chronic:CAUSES EYE IRRITATION, DRYING OF SKIN,
HEADACHE, DIZZINESS, NAUSEA, VAPOR MAY BENARCOTIC. CHRONIC:
RESPIRATORY TRACT IRRITTION, COULD DAMAGE LIVER AND KIDNEYS
Explanation of Carcinogenicity:NO
Effects of Overexposure:CAUSES EYE IRRITATION, DRYING OF SKIN,
HEADACHE, DIZZINESS, NAUSEA. VAPORS MAY BE NARCOTIC. CHRONIC:



RESPIRATORY TRACT IRRITATION, COULD DAMAGE LIVER & KIDNEY DIZZY FEELING, IRRITATION AND REDNESS OF SKIN, PALE AND NAUSEOUS Medical Cond Aggravated by Exposure: KIDNEY, LIVER & LUNG PROBLEMS

First Aid

First Aid: EYES & SKIN: FLUSH WITH PLENTY OF WATER. INHALATION: REMOVE TO FRESH AIR BEGIN ARTIFICIAL RESPIRATION IF NEEDED. AND INGESTION: DO NOT INDUCE VOMITING GET MED- ICAL ATTENTION.

Fire Fighting

Flash Point Method:TCC Flash Point: 102 F 8.89 C Lower Limits: 6.0 Upper Limits: 0.7

Extinguishing Media: CO2, FOAM, AND DRY-CHEMICAL

Fire Fighting Procedures: COOL CONTAINERS WITH WATER SPRAY

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY BURST, IF EXPOSED

TO EXTREME HEAT, ISOLATE FROM HEAT, AND SPARKS

Accidental Release

Spill Release Procedures: PICK UP SPILLED MATERIAL INTO METAL CONTAINER. AVOID SPARKS, FLAME, HOT SURFACES. WIPE OFF RESIDUE WITH BAG

Handling

Handling and Storage Precautions: COMBUSTIBLE, KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME. USE ADEQUATE VENTILATION, AVOID PROLONGED OR REPEATED CONTACT. KEEP CONTAINERS CLOSED.

Other Precautions: STORE IN SECURE AREA. DISPOSE OF EMPTY CONTAINERS SAFELY. KEEP AWAY FROM CHILDREN.

Exposure Controls

Respiratory Protection: SELF CONTAINED BREATHING APPARATUS FOR

CONCENTRATIONS ABOVE TLV LIMITS

Ventilation:LOCAL EXHAUST RECOMMENDED. MECHANICAL, ASSURE FRESH AIR

CIRCULATION

Protective Gloves: RUBBER RECOMMENDED Eye Protection: GOGGLES RECOMMENDED

Other Protective Equipment: NA

Work Hygienic Practices: DO NOT EAT, DRINK NEXT TO MATERIAL, WASH HANDS,

FACE AFTER WORK

Supplemental Safety and Health

OSHA: CLASS II COMBUSTIBLE LIQUID. DOT: COMBUSTIBLE LIQUID, N.O.S. NA

1993

Chemical Properties

Boiling Pt:B.P. Text:311-370 F Melt/Freeze Pt:M.P/F.P Text:120 F

Vapor Pres:2

Vapor Density: 4.7 Spec Gravity: 0.768

Evaporation Rate & Reference: 0.21

Solubility in Water: NEGLIGIBLE

Appearance and Odor: PLIABLE PASTE, SLIGHT SOLVENT ODOR

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid: HEAT, SPARKS, AND OPEN FLAME

Hazardous Decomposition Products: THERMAL DECOMPOSTION MAY YIELD CARBON MONOXIDE

Disposal

Waste Disposal Methods: INCINERATE OR USE SANITARY LANDFILL FOR CONTAMINATED RESIDUE, ACCORDING TO LOCAL, STATE & FED. REGULATIONS. (EPA WASTE NO D001)



Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.